

PRIMARY CORNER DESCRIPTION Sec. Cor. for 23, 24, 25 and 26

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1435)

-----  
Set post cor. of secs. 23, 24, 25 and 26, from which  
A Fir 20" dia., bears S.37°E., 39 lks. dist.  
A Fir 40" dia., bears N.60°E., 36 lks. dist.  
A Fir 36" dia., bears N.30°W., 45 lks. dist.  
A Cedar 30" dia., bears S.47°W., 108 lks. dist.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - V. Tracy, C. Putnam, crew - Aug. 1961 - C.S. file 49/143-44

-----  
Found - 1½" Bolt with nut on top. (Unrecorded, no record source found, April 1995, J.Crawford; V.Laugen)  
Fir, now 38", N.30°W., 29.7 ft. with old bark scribing "S2 26 6". Rescribe this tree in bark "T22S R6W S23 CS BT"  
Fir now 48", N.60°E., 23.8 ft. bark scribing visible "S24 T26 S BT" (old scribing)  
Fir stump, 32" dia. S.37°E., 25.7 ft. cut low, no scribing found.  
Cedar snag 60", whole side facing corner burned off, no scribing.  
New BTs -8" W.Fir N.85°E., 12.3 ft. mkd. T22S R6W S24 CS BT.  
16" W.Fir S.38°E., 49.2 ft. mkd. T22S R6W S25 CS BT  
8" D.Fir S.49°W., 40.0 ft. mkd. T22S R6W CS BT S26.  
Did Not Set Brass Cap.

Fd. bolt, Aug. 1990, M 110-47

BLM Resurvey by Dale T. Bedell, Cadastral Surveyor, under Group #1702, Surveyed July/Aug. 1993 - (DCSO records Vol. 51 Page(s) 19432)

-----  
At the original sec. cor., perpetuated and recorded by Godfrey in 1961, monumented with an iron bolt, 1½" dia., firmly set, with a nut attached to the top, projecting 8" above the ground, from which the remains of the original bearing trees:

- A Fir 56" dia., bears N.60°E., 30 lks. dist., with illegible scribe marks visible on the bark. (Rec. 36 lks.)
- A Cedar snag 60" dia., bears S.47°W., 108 lks. dist., with a burned out blaze.
- A Fir stump 34" dia., bears N.30°W., 45 lks. dist., with scribe marks T22S R6W S23 CS BT visible on the bark, remarked by Godfrey.

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 23, 24, 25 and 26

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

and the remains of bearing trees mkd. by Godfrey:  
A rotted Fir stump 8" dia., bears N.85°E., 18½ lks. dist.,  
no visible marks.  
A Fir 24" dia., bears S.36°E., 74½ lks. dist., with a  
healed blaze.  
A Fir 12" dia., bears S.51½°W., 59 lks. dist., with a  
healed blaze.

At the corner point  
Set an stainless steel post, 28" long, 2 1/2" dia., 22" in  
the ground, with brass cap mkd:  
T22S R6W  
S 23 | S 24  
S 26 | S 25  
1993

from which a new bearing tree  
A Fir 8" dia., bears N.39°W., 18 lks. dist., mkd. T22S R6W  
S23 BT.  
Deposit the iron bolt alongside the stainless steel post.

Fd. OK, Oct. 2007, R Betz, M154-40 (replaces M116-29)

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral  
Surveyor, under Group No. 2500, Surveyed July/Aug. 2010 -  
(DCSO records Vol. 57 Page(s) 22809 & Survey plat 2012-1)  
-----

The cor. of secs. 23, 24, 25, & 26, monumented with an iron  
post, 2½" dia., firmly set, projecting 4" above ground, with  
a brass cap (properly) mkd.

from which the remains of the original bearing trees  
A fir, 48" dia., bears N.60°E., 23.8 ft., with no marks  
visible. (Record, 56" dia., 19.8 ft.)  
A hollow and burnt cedar snag, 43" dia., bears S.47°W.,  
71.3 ft., with no marks visible.  
A sawed, decayed fir stump, 31" dia., bears N.30°W., 29.7  
ft., with scribe marks T22S R6W S23 CS BT visible on  
bark blaze.

and the remains of bearing trees mkd. by Godfrey, in 1961  
A decayed fir stump, size indeterminate, bears N.85°E.,  
2.2 ft., with no marks visible.  
A fir, 29" dia., bears S.36°E., 49.2 ft., with a healed  
double blaze.  
A fir, 2" dia., bears S.51½°W., 38.9 ft., with a healed  
double blaze.

and a bearing tree mkd. by Bedell  
A fir, 12" dia., bears N.39°W., 11.9 ft., with a healed  
blaze.

NAD 1983 (CORS) 96) Lat: 43°38'06.12"N Long: 123°22'04.69"W

Fd. BC & 4 BTs 1/2016 - M170-33 by D. Edwards