

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 23 and 24

Alias	Description
Alias	Description
Alias	Description
Alias	Description

<p>GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1436)</p> <p>-----</p> <p>Set ¼ sec. post, from which A Fir 5" dia., bears N.64°E., 24 lks. dist. A Fir 6" dia., bears N.24°W., 15 lks. dist.</p>
<p>Wilford N. Haines - Surveyed Dec. 1958 - M 14-23</p> <p>-----</p> <p>Found - Iron pipe and scribed stake. Old BTs have been knocked down by logging operation. Set Lot Marker, 1" x 1" x 36" T Iron with brass cap inscribed: Survey Point-Haines #239. Scribed -15" Fir S.44°W., 96.4 ft. 12" Fir N.19°E., 21.7 ft.</p>
<p>BLM Resurvey by Dale T. Bedell, Cadastral Surveyor, under Group #1702, Surveyed July/Aug. 1993 - (DCSO records Vol. 51 Page(s) 19433)</p> <p>-----</p> <p>The orig. ¼ sec. cor., perpetuated and recorded from evidence no longer in existence by Haines in 1958, monumented with a T shaped iron rod, 1" dia., firmly set, projecting 8" above the ground, with a brass disk attached to the top, mkd. WILFORD N HAINES 239 SURVEY POINT DRAIN ORE, from which bearing trees mkd. by Haines: A Fir 25" dia., bears N.19°E., 33 lks. dist. with a healed blaze. A Fir 22" dia., bears S.44°W., 146 lks. dist., mkd. ¼ S BT on the bark.</p> <p>At the corner point Set an stainless steel post, 28" long, 2 ½" dia., 24" in the ground, with brass cap mkd: T22S R6W 1/4 S 23 S 24 1993</p> <p>Deposit the iron rod alongside and white "DEEP-1" magnetic marker at base of stainless steel post. The corner is located in a wire fence line bearing E. and W.</p>
<p>Found OK by K. Hoffine, Feb. 2001 M136-56 Note: new dirt road bears north approximately 60 ft.</p>