

TOWNSHIP 22 RANGE 06 POINT IDENTIFIER # 600440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 13 and 14

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1436)

Set ¼ sec. post, from which
A Fir 30" dia., bears N.85°W., 60 lks. dist.
A B.Oak 24" dia., bears S.73°E., 40 lks. dist.

O.F. Thiel - For: Kent and Wisegarver - Sept/Nov. 1924 - Field Book 115 Page 157

At ¼ cor. bet. 13 and 14, Set a stone for cor. NE tree standing, other fallen but found stump of other tree.

O.F. Thiel - For: Vernon Goodrich, Morningstar Estate - Aug. 1944 - Field Book 118 Page 21

Stone in place, both old trees down.

Ben B. Irving, Douglas Co. Surveyor - Wit: W.S. Crear; Geo. Montgomery - C.S. File 2/49 and Vol. 3 page 284

Identified by a plain sandstone rock set by Thiel and on O.B.T., a 32" B.Oak. This Oak had been chopped out and John Clayton, the owner of adjoining property testified that when Thiel chopped out the tree, scribe marks were visible. Fir BT gone but found old stump burned off level with ground which checked both bearing and distances.
Chiseled the rock 6" x 10" x 15" with an X and ¼.
Scribed -A 15" Fir N.81°E., 55.0 ft. ¼ S13 CS BT.
A 30" Fir S.60°12'W., 266 ft. ¼ S14 CS BT.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - V. Tracy & C Putnam, crew - Aug. 1-2, 1961 - C.S. File 49/143-37

Found - Rock as called for in Irving's renewal in 1928.
Fir stump now 28", N.81°E., 55 ft., showing good scars. Cut open and found good scribing "S"
42" Fir stump S.60¼°W., 266 ft., no scribing or scars found.

Set Brass cap at cor. mkd: County Surveyors Office
T 22 S R 6 W
¼ S14 | S13
1961

Place marked rock alongside.
New BTs -5" D.Fir N.20°E., 10.0 ft. mkd. ¼ S13 CS BT.
7" Madrone S.82½°W., 11.4 ft. mkd. ¼ S14 CS BT.
Corner is in fence corner. Fences N., S., and E. from corner.

TOWNSHIP 22 RANGE 06 POINT IDENTIFIER # 600440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 13 and 14

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Fd. OK, August 1981, R. Dean, M 88-65
Bruce Shaner - 11/16/1999 - C.S. File 65/23-17 ----- Found - Brass cap with corner rock alongside from which a: 18" D.Fir BT (rec. 5") bears N.20°E., 10.0 ft., face overgrown. 12" Madrone BT (rec. 7") face overgrown, bears S.82½°W., 11.4 ft. Corner is in fence corner. Fences bear North, South & East. Corner is at fence line junction at SW corner of clearing, 300 ft. ± SW of a fine home.
Fd. BC & 2 BTs by Carl Sweeden, 1/2006 - M151-35