

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1, 2, 11 and 12

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1438)

-----

Set post cor. of secs. 1, 2, 11 and 12, from which  
A R.Fir 30" dia., bears S.67°W., 13 lks. dist.  
A W.Oak 24" dia., bears N.40°E., 40 lks. dist.  
A B.Oak 12" dia., bears N.33°W., 55 lks. dist.  
A Fir 5" dia., bears S.29°E., 74 lks. dist.

Reported as not found by DCSO, Milo Godfrey, 8/1961 - C.S. File 49/143-2

Robert G. Dean, L.S. #1808 - For: Don Churchill - Aug. 28, 1981 - C.S. File 58/204 and M 88-65

-----

Condition Report Only  
Found - An Oak root crown and charred stump bears N.40°00'E., 26.40 ft.  
Ashen remains of large Fir stump bears S.58°21'W., 8.85 ft. (Orig. rec. 30" R.Fir S.67°W., 8.58 ft.)  
Old fence corner post bears S.53°E., 0.91 ft. (fourway intersection)  
New fence corner post bears N.58°E., 0.86 ft.  
An Oak stump, not BT, bears N.36°09'E., 27.57 ft.  
Ridge top bears West 184 ft. (Rec. West, 283.80 ft.)

Per DCSO office, L. Monrean, deputy, Sept. 16, 1981, C.S. File 61/27-43 - "Evidence not considered conclusive evidence of original corner to perpetuate".

Douglas Co. Surveyors Office - Larry E. Monrean, Deputy - Wit: J.R. Lundeen - Aug. 29, 1983 - C.S. File 62/9-2

-----

Found - No original monument found.  
Found 4-way intersection referenced by Dean's 1981 survey.  
Set temporary hub at position N.53°W., 0.91 ft. from old fence post and S.58°W., 0.86 ft. from new fence post.  
Found - Orig. Oak, now a charred root crown, bears N.40°E., 26.4 ft., no scribing found.  
Evidence of a charred root system at position of original 30" dia. Fir, bears S.67°W., 8.6 ft.  
The attached letter and map in the C.S. File, from the U.S. Geological Survey Mapping Division, show a scribed post at the fence intersection in 1952. With this additional information and evidence found on location, we determine to set a monument at the referenced position.  
(Cont. Next Page)

TOWNSHIP 22 RANGE 06 POINT IDENTIFIER # 600600

PRIMARY CORNER DESCRIPTION Sec. cor. for 1, 2, 11 and 12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Set a 1" x 36" Iron pipe with brass cap protruding 12" above ground, cap mkd: "Douglas Co. Surveyor T22S R6W S1 S1 S11 S12 1983" This monument is set at position of temporary hub determined from found references per M 88-65 and C.S. 58/204. New BTs -A 6" dia. Maple double blazed and scribed "S2 CS BT" bears N.9°W., 8.0 ft.

An 18" B.Oak double blazed and scribed "T22S R6W S12 CS BT", bears S.11°E., 70.0 ft.

A 28" dia. Maple double blazed and scribed "T22S T6W S12 CS BT", bears S.56°E., 55.9 ft.

Fd. OK by J. Branch, Feb. 1999 - M129-33

Fd. OK by H. Christensen, Oct. 2004 -M145-69