

PRIMARY CORNER DESCRIPTION Center 1/4 Corner Section 36

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Ken Hoffine, L.S. 2291 - For: Lone Rock Timber Co. - Aug 1994
- M 120-79

Set 5/8" x 36" rebar w/alum. cap which reads LRT C ¼ S36 1993
PLS 2291., from which

10" D.Fir, bears S.69°35'E., 24.7', I tagged & scribed C¼
S36 BT.

10" D.Fir, bears S.8°14'E., 26.8', I tagged & scribed C¼
S36 BT.

15" D.Fir, bears S.70°39'W., 34.4', I tagged & scribed C¼
S36 BT.

13" D.Fir, bears N.1°35'W., 7.6', I tagged & scribed C¼
S36 BT.

Corner lies on 30% SE side slope approximately 40' North of
shallow swale.

Ken Hoffine, L.S. 2291 - For: Lone Rock Timber Co. -
2/13/2004 - C.S. File 65/49-24

Found - 1994 Lone Rock Timber 2½" alum. cap.

20" D.Fir, bears S.70°39'W., 34.36', as recorded.

10" D.Fir, bears S.69°35'E., 24.69', is down &
uprooted.

10" D.Fir, bears S.8°14'E., 26.79', is down &
uprooted.

13" D.Fir, bears N.1°35'W., 7.6', is down &
uprooted.

New BTs- 9" D.Fir bears N.85½°E., 16.35', we scribe BT & tag
tree.

20" D.Fir bears N.9½°E., 45.20', we scribe BT & tag
tree.

Note - Corner lies on SE slope approx. 40 ft. north of
shallow swale.