

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 24 and 25

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1435)

Set ¼ sec. post, from which
 A Fir 30" dia., bears S.5°W., 137 lks. dist.
 A Maple 12" dia., bears N.30°E., 148 lks. dist.

O.F. Thiel - For: Whipple and Harlan - Feb. 1929 - Field Book 116 Page 41

SE bearing tree standing. Set Dogwood post.

Douglas Co. Surveyors Office - Milo Godfrey - Oct. 12, 1961 (information added 1/16/2001) - C.S. File 49/143-90

Found Haines' T iron w/cap. Two trees near with cruiser's marks. No trace of orig. BTs. No renewal BTs found.

James A. Branch, For: U.S. National Bank - November 25, 1992 M 116-29; C.S. File 63/149-1J

Set 5/8" x 30" rebar with yellow plastic cap marked "Branch Eng. LS 1138".
From which -
 An 11" Fir bears S.12°W., 45.3 ft. scribed "1/4 S25 BT"
 A 6" Fir bears N.38°E., 26.5 ft. scribed "1/4 S24 BT".
 A 22" Fir bears N.32°W., 59.1 ft.
 An 11" Fir bears S.15°W., 31.2 ft.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 12/11/2000 - C.S. File 66/19-1

Found - Haines "T" iron protruding 14" above ground (no rec) 5/8" iron rod with yellow plastic cap "BRANCH ENG 1138" protruding 1" above ground. Set in 1992 (M116-29) IR bears S.38½°W., 34.5 ft. from "T" iron.

From "T" iron

30" now 48" dia., 2½ ft. tall partially rotted D.Fir stump. Searching type axe marks found near the exterior of stump. We open to 15" from center and find burlwood & an old blaze with faint scribed marks, a line and a partial arc. A good chaining notch is found at bottom of blaze, bears S.4¼°W., 87.1 ft. from "T"-iron. (rec. S.5°W., 90.4 ft.) OBT

continued next page

TOWNSHIP 22 RANGE 06 POINT IDENTIFIER # 640300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 24 and 25

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New BTs- **FROM "T" IRON**

7" dia., Hemlock (M116-29 NE BT) w/fully healed double blaze on SW trunk bears S.41½°W., 7.6'. We single blaze facing "T" iron & scribe "X CS BT" 24" dia., D.Fir (M116-29 NW BT) w/fully healed double blaze on SE trunk bears N.65°W., 56.9'. We single blaze facing "T" iron & scribe "X CS BT" 24" dia., D.Fir single blazed & scribed "¼ S24 CS BT" bears N.55°E., 24.9 ft.

Note - Corner lies on a steep NE slope. CS 49/143 refers to 1961 corner search (added to recs on 1/16/2001) We agree w/brg's & dist. taken by Ken Hoffine using EDM for distances, brg's based on GPS. BT tags facing "T" will have small diff. in brg & dist. from this renewal record.

Fd. OK, Oct. 2007, R Betz, M154-40 (**replaces M116-29 & C.S. FILE 63/149-1J**)