

TOWNSHIP 22 RANGE 06 POINT IDENTIFIER # 640500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 12 and 13

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1437)

-----  
Set ¼ sec. post, from which  
A Fir 6" dia., bears N.14°E., 33 lks. dist.  
A Fir 24" dia., bears S.10°E., 47 lks. dist.

O.F. Thiel - For: Kent and Wisegarver - Sept/Nov. 1924 - Field Book 115 Page 157

-----  
NE tree standing. Other gone. Set Cedar Post.

O.F. Thiel - For: Wilbur H. Lewis - Aug. 1946 - Field Book 2 Page 28

-----  
At ¼ cor. bet. 12 and 13, Old stake set by my self by a big Yew post. NE tree standing. W.Oak 40" S.1°or2°W.

Ben B. Irving, Douglas Co. Surveyor - Wit: R.L. Irving; Jess Widdy - Vol. 3 Page 284 and C.S. File 2/49

-----  
Identified by a 4" Cedar post as set by Surveyor Thiel and the O.B.T:  
A 36" leaning Fir N.14°E., 33 lks. I did not chop out this BT as there was no doubt as to its being the O.B.T. Remarked this tree in bark "¼ S12 CS BT".  
Also marked a 16" W.Oak for a BT, South 94.8 ft. "¼ S13 CS BT".

Wilford N. Haines - For: Don Levenhagen - Jan. 21, 1958 M 7-65

-----  
Found - Post and two BTs.  
Set 1" x 1" x 36" Iron with brass cap by post.

Douglas Co. Surveyors Office - Gary E. Commons; P. Earle; Gary Langlitz, crew - Jan. 10, 1975 - C.S. File 57/17-4

-----  
Found - Haines T-Iron with copper washer cap.  
Orig. BT, 36" D.Fir now 40" N.14°E., 21.8 ft. Has well healed scar which was not opened. Bark scribe visible reading ¼ S12 CS. Haines copper cap nailed to tree.  
W.Oak BT, 16" South, 94.8 ft. is now a 26" stump. Inside rotted, shows good reverse scribe.  
New BT - 25" D.Fir N.46°W., 25.8 ft. scribed ¼ S12 CS BT.  
Corner is outside NE corner of pasture. Fences bears West and South from fence corner.

TOWNSHIP 22 RANGE 06 POINT IDENTIFIER # 640500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 12 and 13

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Douglas County Surveyors Office - Gregory Quibell and Randy Smith, crew - Nov. 15, 1982 - C.S. File 62/1-31

-----

Found - Haines T Iron with copper cap.  
Orig. 6" (maybe 36") now 40" Fir with well healed blaze. Also bark scribed "¼ S12 CS" bears N.14°E., 21.8 ft.  
16" W.Oak now 26" rotted remains of stump, bears South, 94.8 ft.  
25" Fir now windfall with partially healed blaze bears N.46°W., 25.8 ft. to root hole.  
I reference found T-Iron, then Set 1" x 30" I.Pipe with brass cap in its place. Cap mkd: "Douglas Co Surveyor T22S ¼ S12 S13 R6W 1982" I reset found T-Iron along South edge of brass cap and slightly lower.  
New BTs -15" Fir scribed "¼ S12 CS BT" in double blaze bears N.30°W., 86.9 ft.  
6" W.Oak scribed "¼ S13 CS BT" in double blaze bears S.56°E., 6.8 ft.  
8" double W.Oak scribed "¼ S13 CS BT" in double blaze bears S.70°E., 23.0 ft.  
DCSO BT tags on all trees. Sketch in C.S. File.

Fd. OK by J. Branch, Feb. 1999 - M129-33  
Fd. OK by D. Edwards, April 2005 - M147-61  
FD BC by C. Woodruff 10/2016 - M172-53