

TOWNSHIP 22 RANGE 06 POINT IDENTIFIER # 700100

PRIMARY CORNER DESCRIPTION CC for Sec 36,; & Sec 31, T22-5

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1383)

Set Post C C. of T.22S R6 and 6 W, from which
A Fir 3" dia., bears N.51°E., 71 lks. dist.
A B.Oak 15" dia., bears N.17°W., 118 lks. dist.

BLM resurvey by Otis Gould, Joseph Gawron, and Orville Eggen, Cadastral Surveyors, under Group #244, surveyed June 1943/October 1957 (DCSO records Vol. 30 Page(s) 12623)

The closing cor. of T22S R5W & R6W, determined at record bearing and distance from the only remaining bearing tree
A Fir 48" dia., bears N.51°E., 71 lks., marks grown over.
At the corner point
Set an iron post, 3 ft. long, 3" dia., 27" in the ground, with brass cap mkd:

C C
T22S
R6W | R5W
S36 | S31
T23SR6W
S 1
1943

from which
A Fir 20" dia., bears N.56½°W., 237 lks., mkd. T22S R6W S36 CC BT.

Survey by Bruce Rogers - Wit: Wm. Stoffel and M. Stone - Feb. 1965 - C.S. File 53/101-24

Found - GLO brass cap at corner.
20" Fir, now stump, N.56½°W., 156.4 ft., scribing visible.
Corner is 2 ft. South of E-W fence.
New BTs -7" D.Fir N.4°W., 26.0 ft. mkd. CC T22S R6W S36 CS BT
6" Madrone N.62°E. 22.5 ft mkd CC T22S R5W S31 CS BT

Fd. OK, June, 1981, E. Bloom, M 79-79
Fd. OK, Feb. 1986, E. Bloom, M 100-25

Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 6/12/2003 - C.S. File 66/58-12A&B

Found - 1943 BLM brass cap iron pipe
continued next page

TOWNSHIP 22 RANGE 06 POINT IDENTIFIER # 700100

PRIMARY CORNER DESCRIPTION CC for Sec. 36, ; & Sec. 31, T22-5

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

3"? now 60" dia., 3 ft. high D.Fir stump with a well
healed single blaze, we open & find old blaze
with illegible circular scribing & a line 24"
from center (OBT) bears N.54°E., 48.9 ft. to
center, 46.9 ft. to blaze. (rec. N.51°E. 46.9 ft)
20" now rotted D.Fir remains no blazes or scribing,
found near record N.56½°W., 156.4 ft. 1943
7" now 19" dia., D.Fir with a fully healed double
blaze, bears N.4°W., 26.0 ft. (1965)
6" now 14" dia., madrone with a fully healed blaze,
bears N.62°E., 22.5 ft. (1965)
New - 14" dia., Madrone double blazed & scribed "CC T22S
R6W S36 CS BT" bears N.9°W., 10.7 ft.
Following positions are for location purposes only
NOT SURVEY GRADE
Equipment: Trimble GEOEXPLORER 3 System
File: R061223A
Point Name: CC T22SR5W S31 T22SR6W S36
1927 1983
OCS N 719647 E 1246066 N E
Latitude: 43°36'22.1" Latitude:
Longitude: 123°20'49.4" Longitude:
Offset to corner? yes
Corrected for? yes