

PRIMARY CORNER DESCRIPTION Sec Cor for 13 & 24; 18 & 19, T22-5

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1384)

 Set post cor. of secs. 13, 18, 19 and 24, from which
 A W.Oak 8" dia., bears S.34°W., 228 lks. dist.
 A W.Oak 24" dia., bears N.48°W., 175 lks. dist.
 A W.Oak 24" dia., bears S.51½°E., 315 lks. dist.
 A W.Oak 18" dia., bears N.15°E., 228 lks. dist.

Douglas Co Surveyors Office - James Byron, Deputy - Crew Milo Godfrey; S.A. Bilow - April 13, 1959 - C.S. File 49/143-35

 Found - Orig. 18" now 22" partly rotted Oak stump, N.15°E., 150.5 ft I open near base & find good scribing "BT"
 Orig. 24" now 30" partly rotted Oak snag, N.48°W., 115.5 ft., I open near base and find good scribing "BT".
 30" down Oak, checks brg. and dist. for orig. SE BT
 No trace of original SW BT.

Set Brass cap at cor. mkd: County Surveyors Office

	T 22 S		
R6W	S 13 S 18	R5W	
	S 24 S 19		
	1959		

New BTs -9" double W.Oak bears N.28°E., 12.0 ft. scribed S18 T22S R5W CS BT.
 9" W.Oak bears S.57°E., 7.9 ft. scribed S19 T22S R5W CS BT.
 22" R.Fir bears N.25½°W., 19.4 ft. scribed S13 CS BT
 This BT scribed on one face and scribed high, above fence.
 10" W.Oak bears S.25°W., 32.0 ft. scribed S24 T22S R6W CS BT.

I find 3/4" Iron rod S.8½°W., 71.3 ft. from brass cap. I rod in fence corner, fences running East, South & Northwesterly.

Fd. OK, March 11, 1965, DCSO, B.Rogers, C.S. File 53/101-87
 Fd. OK, Aug. 1981, B.Shaner, M 90-2
 Fd. OK, Dec. 1991, C.Guile, Land partition, 1992-0079 A & B.
 Fd. OK, May 1998 by C.Sweedeen - P.Platt 1998-0049
 Fd. Ok by D. Edwards - 11/2005 - M149-22

DCSO-GIS Corner visitation - 11/1/2005 - Typed: 1/13/2011 - C.S. File 67/33-1

 Monument - 1¼" IP W/BC Comment - OK