

TOWNSHIP 22 RANGE 06 POINT IDENTIFIER # 700700

PRIMARY CORNER DESCRIPTION NE Tsp. cor. (NE. Cor. Sec. 1)

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 2 Page(s) 691)

-----  
Set post cor. of townships 21 and 22 S., Ranges 5 and 6 W.; from which

A B.Oak 7" dia., bears N.26½°E., 198 lks. dist.

A W.Oak 24" dia., bears S.13°W., 210 lks. dist.

A W.Oak 20" dia., bears S.7½°E., 145 lks. dist.

No tree near in T.21 S., R.6 W.

-----  
F.C. Frear, Deputy Co. Surveyor - Wit: J.W. Harness; Earl Frier - Dec. 1917 - Vol. 3 Pg. 3; C.S. File 1/4 and M 1-6

-----  
Renew from old BTs.

Set in a 1½" x 30" Galv. I.P. from which

A 14" Fir bears N.15°W., 95 lks. dist.

A 24" W.Oak bears S.13°W., 2.10 chs. dist.

A 20" W.Oak bears S.7½°E., 1.45 chs. dist.

-----  
O.F. Thiel - For: I.W. Hains - Oct. 25, 1943 - Field book 117 Page 63

-----  
At NE cor. of sec. 1, T22-6, buried a stone 8 x 14 x 14 in road & gate. SE and SW trees standing.

-----  
Douglas Co. Surveyors Office - James Byron, Deputy - Crew, Milo Godfrey; S. Bilow - For: W.E. Clevenger - June 19, 1959 - C.S. File 49/158 and M 15-18

-----  
Found - Orig. 20" now 40" W.Oak S.7½°E., 95.7 ft., shows good scar, I do not open.

Orig. 24" now 40" Oak stump, S.13°W., 138.6 ft., I open near base and find good scribe marks "D 1".

Also find stone with + on top at corner set by Haines, 1943. (corner stone in N-S fence by gate)

New BTs -40" R.Fir bears S.21°E., 31.0 ft. scribed S6 T22S R5W CS BT.

8" R.Fir bears N.72°E., 56.0 ft. scribed S31 T21S R5W CS BT.

10" B.Oak bears S.28°W., 18.8 ft. scribed S1 T22S R6W CS BT.

8" W.Oak bears N.2°W., 10.0 ft., S36 T21S R6W CS BT.

-----  
Fd. OK, Aug. 1981, R.Dean, M 88-65

-----  
Fd. OK, Feb. 1992, D.Peel, M 114-60 (Cont. Next Page)

PRIMARY CORNER DESCRIPTION NE Tsp. cor. (NE Cor. Sec. 1)

Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_

Douglas Co. Surveyors Office - Randall Smith and Stephen Flause, Deputies - Nov. 2, 1990 - C.S. File 64/58-1

-----  
 Found - 14" x 14" x 7" stone with probable "+" mkd. on side. Stone appears to have been tipped over and is in two pieces. Stone was found 1 ft. below ground. 40" now 47" dia. D.Fir with a fully healed single blaze, bears S.21°E., 31 ft.  
 8" now 21" dia. D.Fir, with a fully healed double blaze, bears N.72°E., 56 ft.  
 10" now 15" dia., B.Oak with a fully healed double blaze, bears S.28°W., 18.8 ft.  
 8" now 12" dia. W.Oak with a fully healed single blaze bears N.2°W., 10 ft.  
 24" now 24" dia., 14" high rotted Oak stump with axe marks visible, bears S.13°W., 138.6 ft. OBT.  
 20" now 40" dia., W.Oak with a fully healed blaze, bears S.7½°E. 97.9 ft. (Rec. S.7¼°E. 95.7 ft) OBT  
 Set a DCSO 2 3/8" dia., brass cap on a 1¼" O.D. x 31" long I.P. is set flush with ground, with corner stone reset upright along East edge of BC/IP 3" below ground. Cap mkd:

DOUGLAS COUNTY SURVEYORS

R	T21S	R
6	<u>S36</u>   <u>S31</u>	5
W	S01 S06	W
	T22S	

OFFICE 1990

Corner lies in middle of old gravel road at North-South fence crossing.

**Above corner visit notes not recorded until Jan. 1995. DCSO visit also made to this corner March 16, 1992 and filed in C.S. File 64/24-2, same information.**

Fd. OK, Nov. 10, 1994, M 121-21

Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 9/4/2001 - C.S. File 66/29-1

-----  
 Found - 1990 DCSO brass cap/iron pipe fd. bent & out of ground. 1943 stone not found.  
 BTs found as rec'd in 1990 exception being 1959 Fir BT bears N.69½°E. 56.0 ft. (rec. N.72°E. 56.0 ft)  
 Set - 5/8" by 30" long iron rod with DCSO alum. cap set 4" below road surface near center of road.  
 Rust and old flagging found in hole.  
 Compass decl. 17½°E.  
 Top of alum. cap stamped:

2001
<u>36</u>   <u>31</u>
1 6

cont.

TOWNSHIP 22 RANGE 06 POINT IDENTIFIER # 700700

PRIMARY CORNER DESCRIPTION NE Tsp. cor. (NE. Cor. Sec. 1)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

DCSO-GIS Corner visitation - 5/18/2004 - Typed: 1/12/2011 -  
C.S. File 67/33-1

-----  
Fd. 5/8" rebar - FD. OK

Fd. AC/IR buried in dirt road as described per C.S. 66/29-1,  
buried in dirt road and rec. BTs. 11/2014 by Corey Woodruff,  
M168-64