

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 043040

PRIMARY CORNER DESCRIPTION SE cor. George H. Bartgis DLC #43

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Surveys of Donation Land Claims by - Dennis Hathorn, Deputy,
dated Sept. 1856

At the SE cor. in Sec. 18, set post, from which
A Fir 12" dia., bears N.80°W., 52 lks.
A Fir 10" dia., bears N.10°E., 58 lks.

Wilford N. Haines - For: R.D. Hungerford - March 1967 -
M 32-72

Found - Two original bearing trees, both now stumps.
Set ½" steel rod for corner.
NE cor. DLC #41, 92.0 ft. West of this corner.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy, Jack
Heritage, E. West, crew - April 4, 1967 - C.S. File 54/41-1

Found - 1/2" I.Rod at corner set by Haines.
Orig. 10" now 40" Fir, N.10°E., 38.3 ft.
previously opened many years ago, "W" scribe
visible. We open higher and find "22S 7" scribe
and reverse. Fir, now stump.
Orig. 12" now 40" Fir stump N.80°W., 34.3 ft., not
opened, burl wood visible on top of stump.
New BTs -12" D.Fir S.79°E., 18.4 ft. mkd. SE DLC 43 CS BT.
11" D.Fir S.3°W., 21.4 ft. mkd. SE DLC 43 CS BT.
This corner lies 97.0 ft. East of NE corner DLC #41 and on
northerly slope approx. 150 ft. S. of small stream, course E.

BLM resurvey by Peter A. Peterson, Cadastral Surveyor, under
Group #663, surveyed April/May 1968 (DCSO records Vol. 35
Page(s) 14416)

The SE cor. of Donation Land Claim No. 43, in sec. 18,
perpetuated and recorded by Haines in 1967, monumented with
an iron rod, 30" long, ½" dia. firmly set 24" in the ground,
from which

A sawed Fir stump 38" dia., bears N.10°E., 58 lks. dist.
with scribe marks 22S 7W visible on opened blaze.
A sawed Fir stump 45" dia., bears N.80°W., 52 lks. dist.
with healed blaze.

and trees mkd. and recorded by Tracey in 1967

A Fir 11" dia., bears S.80°E., 28 lks. dist. with frag-
mentary scribe marks visible on open blaze.

(Cont. Next Page)

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 043040

PRIMARY CORNER DESCRIPTION SE cor. Geo. H. Bartgis DLC #43

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

a Fir 12" dia., bears S.3°W., 32 lks. dist. with frag-
mentary scribe marks visible on open blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground,
with brass cap mkd:

T 22 S R 7 W

C 43 | S 18

1968

Deposit the iron rod alongside the iron post.