

PRIMARY CORNER DESCRIPTION Int. Cor. George H. Baratgis DLC #43

| Alias | Description |
|-------|-------------|
| _____ | _____       |
| _____ | _____       |
| _____ | _____       |
| _____ | _____       |

Surveys of Donation Land Claims by - Dennis Hathorn, Deputy,  
dated Sept. 1856

-----  
Set post interior cor. Cl. 43, from which  
An Oak 12" dia., bears N.½"W., 885 lks.  
An Oak 12" dia., bears N.4°E., 910 lks.

BLM resurvey by Peter A. Peterson, Cadastral Surveyor, under  
Group #663, surveyed April/May 1968 (DCSO records Vol. 35  
Page(s) 14419)

-----  
The interior cor. on the E. bdy. of Claim No. 43, determined  
at record bearing and distance from the original bearing  
trees

- A W.Oak 20" dia., bears N.4°E., 910 lks. dist. with  
scribe marks BT visible on opened blaze.
- A stump hole and Oak roots, bears N.0½"W., 885 lks.  
dist.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 22" in the ground,  
and in a mound of stone, 3 ft. base, to top, with brass cap  
mkd: T 22 S R 7 W  
C 43 S 18  
1968

from which

- A Fir 18" dia., bears N.29°E., 540 lks. dist. mkd. T22S  
R7W S7 BT.
  - A Fir 25" dia., bears S.19½°W., 445 lks. dist. mkd. T22S  
R7W C43 BT.
- Set a 6 ft. steel fence post alongside the iron post.