

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 100240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 30; and 25 of T22-8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1499)

Set ¼ sec. post, from which
A W.Oak 15" dia., bears N.58°W., 100 lks. dist.
A W.Oak 6" dia., bears N.31¼°E., 51 lks. dist.

Jesse W. Cole, Deputy Co. Surveyor - Wit: Clyde Beckley; Orval Beckley; Ivan Grubb - Oct. 25, 1915 - C.S. File 1/8; Field Book 34 Pages 47-52 and Vol. 2 Page 234

Renew corner by setting an Oak post, from which the original bearing trees bear as follows:
A W.Oak 15" dia., N.58°W., 100 lks. dist.
A W.Oak 6" dia., N.31½°E., 51 lks. dist.

Douglas Co. Surveyors Office - James Byron, Deputy - Crew, Milo Godfrey; Clete Putnam - June 6, 1961 - C.S. File 52/14-1

Found - Orig. 6" now 30" W.Oak N.31½°W., 33.7 ft., center rotted, no scribing found.
Orig. 15" now 30" W.Oak, N.58°W., 66.0 ft., center rotted, no scribing found.

Both BTs were opened years ago, possibly by Cole and each checks record bearing and distance. Fence to North and to West from corner.

Set Brass cap at cor. mkd: County Surveyors Office
T 22 S
¼ S 25 | S 30
R8W | R7W
1961

New BTs -11" W.Oak bears S.80°W., 16.0 ft. scribed ¼ S25 CSBT
16" W.Oak bears S.24½°E., 36.3 ft. scribed ¼ S30 CS BT.

"I, Henry Beckley, state that the above original BTs have been used for bearing trees for approx. 40 years." (See signed statement in file)

Cor. Fd. and used in BLM resurvey by Brooks and Jelley, under Group #'s 514 and 350, surveyed June 1963/March 1965 (DCSO records, Vol. 33 Page 13676)

Fd. OK by C. Sweeden, Oct. 1999 - M133-33