

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 100500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 7 & 18; 12 & 13, T22-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1501)

Set post cor. of secs. 7, 12, 13 and 18, from which
A W.Oak 18" dia., bears S.71°W., 674 lks. dist.
A Fir 50" dia., bears N.22°W., 954 lks. dist.
Raised mound with trench, as per instructions.

Cor. Fd. OK, in GLO survey by W.H. Byars, under Contract #376 dated Jan. 22, 1881 (DCSO records, Vol. 4 Page 1533)

Ben B. Irving, Deputy Co. Surveyor - Wit: N.E. Richardson; Oliver Haines - Dec. 1929 - Vol. 4 Pg. 4; C.S. File 14/38 and M 6-7

Set an Oak post properly marked and with a ½" x 60" Pipe driven for the corner. Location determined from an old down and partially burned Fir. This tree was shown by J.W. Jones an old resident who had seen the scribe marks many times. Upon measuring out the proper distance, found the remains of an old Oak stump of proper size and position to have been the other BT. Set as new BTs:
A 12" W.Oak S.64°W., 205.5 ft. dist.
A 14" W.Oak S.78°10'W., 176.1 ft. dist.
A 12" W.Oak N.78°51'W., 189.9 ft. dist.
All properly blazed and scribed.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - V. Tracy and C. Putnam, crew - March 1962 - C.S. File 52/14-112

Found - Haines T Iron. (Unrecorded)
19" W.Oak S.64°W., 205.5 ft., shows good scar.
26" W.Oak S.78°W., 176.1 ft., shows good scar.
17" W.Oak N.70°W. (not N.79°W.) 189.9 ft. Has been opened previously, scribing visible "S" and "2"
Blaze and scribe:
9" W.Fir N.59°W., 205.5 ft. mkd. T22S R8W S12 CSBT
Did not Set Brass Cap.

BLM resurvey by Peter A. Peterson, Cadastral Surveyor, under Group #663, surveyed April/May 1968 (DCSO records Vol. 35 Page(s) 14408-09)

The Sec. cor., determined from bearing trees mkd. and recorded by Irving in 1929 when the original bearing trees were still existent.
(Cont. Next Page)

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 100500

PRIMARY CORNER DESCRIPTION Sec. cor. for 7 & 18; 12 & 13, T22-8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

The corner point was perpetuated by Wilford N. Haines about 1961, monumented with a T shaped iron rod, 30" long, firmly set 24" in the ground, from which the trees mkd. by Irving in 1929:

A W.Oak 20" dia., bears S.65°W., 309 lks. dist. with healed blaze.

A W.Oak 26" dia., bears S.79½°W., 265 lks. dist. with healed blaze.

A W.Oak 18" dia., bears N.70½°W., 287 lks. dist. with scribe marks S12 visible on opened blaze.

and a tree mkd. by Godfrey in 1962

A W.Fir 15" dia., bears N.59°W., 311 lks. dist. with fragmentary scribe marks visible on open blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd:

T 22 S
R 8 W R 7 W
S 12 | S 7
S 13 | S 18
1968

Deposit the iron rod and set a 6 ft. steel fence post alongside the iron post.

Cor. tied in BLM survey by Jack W. Bowder, Cadastral Surveyor, under Group #928, surveyed July/Aug. 1977 (DCSO records, Vol. 40 Page 16017)