

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 100540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 7; and 12 of T22-8

Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1501)

Set ¼ sec. post, from which
A W.Oak 24" dia., bears N.7°W., 335 lks. dist.
A Fir 18" dia., bears N.86°E., 701 lks. dist.

GLO survey by W.H. Byars, Deputy Surveyor under contract # 376 survey dated Jan 22, 1881 (DCSO records Vol. 4 Page(s) 1533 and 1534)

Unable to find ¼ sec. cor. or witness trees, set tem. ¼ sec. cor.
Set Fir post, from which
A Fir 15" dia., bears West, 3 lks. dist.
A Fir 12" dia., bears East 10 lks. dist.

Ben B. Irving, Deputy Co. Surveyor - Wit: N.E. Richardson; Oliver Haines - Dec. 1929 - C.S. File 14/38 and M 6-7

Location identified from snag of orig. BT.
Set a plow share for corner.
On account of last summer's fire, there were no live trees in sight of the corner to mark for BTs except by going an excessive distance.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - V. Tracy and C. Putnam, crew - March 1962 - C.S. File 52/14-125

Found - Plow share set by Irving in 1929, nearly buried in ground.
Alongside plowshare, Set brass cap mkd:
County Surveyors Office
T22S ¼ R8W S12 | S7 R7W
1962
Corner lies on open grassy slope. No trees within 500 ft.
Mr. Haines house bears S.10°W., approx. 550 ft. from corner.

BLM resurvey by Peter A. Peterson, Cadastral Surveyor, under Group #663, surveyed April/May 1968 (DCSO records Vol. 35 Page(s) 14410)

The ¼ sec. cor., perpetuated and recorded by Irving in 1919, when the original bearing trees were existent; subsequently remonumented by Godfrey in 1962, with an iron post, 1½" dia., projecting 12" above ground, firmly set, with brass cap, from which new bearing trees
(Cont. Next Page)

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 100540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 7; and 12 of T22-8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A Fir 7" dia., bears N.83°E., 397 lks. dist. mkd. ¼ S7 BT
A Fir 6" dia., bears N.60¼°W., 425 lks. dist. mkd. ¼ S12
BT.
Set a 6 ft. steel fence post alongside the iron post.

Fd. OK, June 27, 1985, L. Roberts, C.S. 63/18-4(B) & M 90-74

Douglas Co. Surveyors Office - John Pike - Stephen J. Flause
- 2/5/2008 - C.S. File 67/25-10

Found 1962 DCSO BC/IP, NW BT OK, NE BT is high stump, corner
lies in area that was recently logged & planted back.