

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 140500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 7 and 18

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1507)

Set $\frac{1}{4}$ sec. post, from which
Set $\frac{1}{4}$ sec. post, deposited charred stake, raised mound with trench and pits as per instructions.

BLM resurvey by Peter A. Peterson, Cadastral Surveyor, under Group #663, surveyed April/May 1968 (DCSO records Vol. 35 Page(s) 14412)

Point for the $\frac{1}{4}$ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd:

$\frac{1}{4}$ $\frac{S 7}{S 18}$
T 22 S R 7 W
1968

from which

A Fir 15" dia., bears N.75°W., 610 lks. dist. mkd. $\frac{1}{4}$ S7 BT.

A Fir 20" dia., bears S.34°W., 508 lks. dist. mkd. $\frac{1}{4}$ S18 BT.

Set a 6 ft. steel fence post alongside the iron post.