

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 6 and 7

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 152 survey dated June 3, 1871 (DCSO records Vol. 4 Page(s) 1526)

Set ¼ sec. post, from which
A Fir 5" dia., bears North, 38 lks. dist.
A Fir 6" dia., bears South, 55 lks. dist.

Wilford N. Haines, #239 - For: Woolley Logging - Dec. 1963 - M 27-34

Not found.
Set 1" x 1" x 36" T Iron.

BLM resurvey by Peter A. Peterson, Cadastral Surveyor, under Group #663, surveyed April/May 1968 (DCSO records Vol. 35 Page(s) 14415)

The ¼ sec. cor., at proportionate distance, reestablished and recorded by Haines in 1963, monumented with a T shaped iron rod, 36" long, firmly set 30" in the ground, from which the Haines bearing tree

A Fir 8" dia., bears S.21°E., 54 lks. dist. with fragmentary scribe marks visible on open double blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

¼ $\frac{S\ 6}{S\ 7}$

T 22 S R 7 W

1968

from which a new bearing tree

A Fir 7" dia., bears N.16°W., 50 lks. dist. mkd. ¼ S6 BT
Deposit the iron rod alongside the iron post.

Tony Hostetter - For: Seneca Jones Timber Co. - 5/2005 - M147-75

Found - 1968 BLM brass cap & both BTs.

New BTs- 18" hemlock, scribed "S6 ¼ BT" bears N.33°E., 25.3 feet to spike.

28" fir, scribed "S7 ¼ BT" bears S.52°E., 18.2 ft to spike.

continued next page

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 140600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 6 and 7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM resurvey by Michael O. Jones, Cadastral Surveyor under special instructions dated May 27, 2009 - Surveyed June/Aug. 2009 - (DCSO records BLM plat 2011 & Vol. 56 Page 22266)

The ¼ sec. cor. of secs. 6 & 7, reestablished by Haines, in 1963, remonumented by Peterson in 1968, and perpetuated by Hostetter, in 2005; monumented with an iron post, 2½" dia., firmly set, projecting 4" above ground, with a brass cap (properly) mkd.

from which a BT mkd. by Haines, and reported by Peterson

A fir, 24" dia., bears S.21°E., 35.6 ft., with a healed blaze.

a BT mkd. by Peterson

A fir, 24" dia., bears N.16°W., 33.0 ft., with a healed blaze.

and BTs mkd. by Hostetter

A hemlock, 13" dia., bears N.35°E., 26.2 ft., with scribe marks S6 ¼ BT visible on partially healed blaze.

A fir, 21" dia., bears S.50°E., 19.1 ft., with illegible scribe marks visible on partially healed blaze.

A steel fence post is alongside the cor.

Latitude 43°40'42.75"N. Longitude 123°34'27.86"W.
(NAD 1983 (CORS 96))