

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 200375

PRIMARY CORNER DESCRIPTION South WC Secs 17, 18, 19, & 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Running north, at 75.00 chs. on line between 19 and 20, the south witness corner for Secs. 17, 18, 19, & 20

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1505)

(Witness corners set for Section corner. True corner on bluff)

Set post bet. secs.19 and 20, from which
A B.Oak 8" dia., bears N.52°E., 19 lks. dist.
A Fir 10" dia., bears N.50°W., 19 lks. dist.

BLM resurvey by Jack W. Bowder, Cadastral Surveyor, under Group #928, surveyed July/Aug. 1977 (DCSO records Vol. 40 Page(s) 16019 and 16021)

(True point for the cor. of secs. 17, 18, 19 and 20, falls on precipitous E. slope, where it is impracticable to establish a permanent monument.)

Point for the witness cor. (between secs. 19 & 20), at proportionate distance; there is no remaining evidence of the original witness corner.

Set an iron post, 28" long, 2 1/2" dia., 22" in the ground, with brass cap mkd:

W C
T 22 S R 7 W
^

S 18 | S 17
S 19 | S 20
1977

from which

A Fir 5" dia., bears N.48°E., 5 lks. dist. mkd. X BT.
A Chinquapin 8" dia., bears S.32°E., 30½ lks. dist. mkd. X BT.
A Fir 9" dia., bears S.30½°W., 31½ lks. dist. mkd. X BT

Fd. Ok by Gerald Riley, May 1998, M 130-17
Fd. Ok by K. DeGroot, 12/2006 - M146-51