

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 200500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 7, 8, 17 and 18

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1506)

Set post cor. of secs. 7, 8, 17 and 18, from which
A Fir 12" dia., bears N.51°E., 118 lks. dist.
A Fir 36" dia., bears N.13°W., 24 lks. dist.
A Fir 30" dia., bears S.46°W., 46 lks. dist.
A Fir 44" dia., bears S.60°E., 82 lks. dist.

GLO survey by W.H. Byars, Deputy Surveyor under contract # 152 survey dated June 3, 1871 (DCSO records Vol. 4 Page(s) 1524)

A fire, having consumed post and witness trees, I drove post and threw up stone mound.

Wilford N. Haines - For: Yoncalla Lumber Co. - March 1961 - M 22-1

Found - Orig. NW and SE BTs. (these BTs scribed in 1855, reported burned in 1871 by Byars)
Set 1" x 1" x 36" T. Iron.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - V. Tracy & Mike Stone, crew - July 13, 1962 - C.S. File 52/14-98

Found - Haines "T" Iron and cap at corner.
Fir now 52", S.64°E., 51.9 ft. (Rec. S.60°E., 54.1 ft.) Tree previously opened and good scribing "S" visible.
Fir now 48", N.17°W., 15.0 ft. (Rec. N.13°W., 15.8 ft.) has been opened previously, good scribing visible, recently rescribed in bark "S7". Haines metal disc on both trees.
Fir now 45", N.51°E., 69.4 ft. (Rec. N.51°E., 77.9 ft.) chopped into but not deep enough to find scribing.
Corner lies on very steep slope and slope distances fit distance calls on trees.
Also find stump hole with rotted Fir wood which fits orig. SW BT.
Blaze and rescribed:
45" Fir, N.51°E., 69.4 ft. mkd. T22S R7W S8 CS BT.

BLM resurvey by Peter A. Peterson, Cadastral Surveyor, under Group #663, surveyed April/May 1968 (DCSO records Vol. 35 Page(s) 14411)

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 200500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 7, 8, 17 and 18

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

The Sec. cor., perpetuated and recorded by Haines in 1961, monumented with a T shaped iron rod, 36" long, firmly set 30" in the ground, from which the original bearing trees:

A Fir 47" dia. bears N.51°E., 108 lks. dist. with no marks visible on opened blaze. (Rec. and slope dist., 118 lks.)

A Fir 55" dia., bears S.63°E., 82 lks. dist. with healed blaze. (Rec. S.60°E.)

A Fir 47" dia., bears N.13°W., 24 lks. dist. with fragmentary scribe marks visible on opened blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 25" in the ground, with brass cap mkd:

T 22 S R 7 W
S 7 S 8
S 18 S 17
1968

No suitable tree available within limits in sec. 18.

Deposit the iron rod alongside the iron post.