TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 200540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 7 and 8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 152 survey dated June 3, 1871 (DCSO records Vol. 4 Page(s) 1525)

Set ¼ sec. post, from which
A Fir 4" dia., bears S.20°E., 5 lks. dist.
A Fir 6" dia., bears S.68°W., 25 lks. dist.

Wilford N. Haines, #239 - For: Woolley Logging Co. - Dec. 1963 - M 27-16

Set 1" x 1" x 36" T Iron, from which scribed
28" Fir S.66°W., 129.9 ft.
14" Fir S.59°E., 119.5 ft.

BLM resurvey by Peter A. Peterson, Cadastral Surveyor, under Group #663, surveyed April/May 1968 (DCSO records Vol. 35 Page(s) 14413-14)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 25" in the ground, with brass cap mkd:

¼
S 7 S 8
T 22 S R 7 W
1968

from which
A Fir 5" dia., bears s.14°E., 59 lks. dist. mkd. ¼ S8 BT
No suitable tree available within limits in sec. 7.

From this point, a corner established and recorded by Haines in 1963, bears S.68°W., 0.09 chs. dist. monumented with a T shaped iron rod, 36" long, firmly set 24" in the ground, from which
A Fir 20" dia., bears S.58½°E., 181 lks. dist. with healed double blaze.
A Fir 35" dia., bears S.67°W., 197 lks. dist. with healed blaze and scribe marks ¼ S visible on bark.