

PRIMARY CORNER DESCRIPTION Sec. Cor. for 5, 6, 7 and 8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 152 survey dated June 3, 1871 (DCSO records Vol. 4 Page(s) 1525-26)

Set post cor. to secs. 5, 6, 7 and 8, from which
A Laurel 10" dia., bears N.72°E., 121 lks. dist.
A Fir 30" dia., bears S.52°E., 140 lks. dist.
A Fir 12" dia., bears S.10°W., 34 lks. dist.
A Fir 12" dia., bears N.20°W., 40 lks. dist.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - V. Tracy and M. Stone, crew - July 17, 1962 - C.S. File 52/14-96

Found - Haines T Iron at corner with no cap. (unrecorded)
Fir now 42", S.52°E., 92.4 ft., very faint bark scribing visible "S8" and "R" legible.
Fir now 36", S.10°W., 22.4 ft., shows very plain scar. Didn't open. Blaze and rescribe this tree "T22S R7W S7 CS BT"
No trace found of NE or NW trees.

Did Not Set Brass Cap

New BTs -14" Hemlock N.15°W., 36.4 ft. mkd. T22S R7W S6 CSBT
18" D.Fir *N.50°E., 26.5 ft. mkd. T22S R7W S5 CS BT.
15" D.Fir S.70°E., 21.4 ft. mkd. T22S R7W S8 CS BT.
Corner lies on very steep SE slope.
*N.40°E. per research 3/26/2018

BLM resurvey by Peter A. Peterson, Cadastral Surveyor, under Group #663, surveyed April/May 1968 (DCSO records Vol. 35 Page(s) 14414)

The Sec. cor., perpetuated and recorded by Haines in 1961, monumented with with a T shaped iron rod, 36" long, firmly set 30" in the ground, from which the remains of the original bearing trees:

A Fir 48" dia., bears S.52°E., 140 lks. dist. with a healed blaze.
A Fir snag 35" dia., bears S.10°W., 34 lks. dist., with healed blaze.
and trees mkd. by Godfrey in 1962
A sawed Fir stump 20" dia., bears N.40°E., 40 lks. dist. with fragmentary scribe marks visible on open blaze.
A Fir 18" dia., bears S.70°E., 33 lks. dist. with fragmentary scribe marks visible on open blaze.
A Hemlock 18" dia., bears N.17°W., 57 lks. dist. with fragmentary scribe marks visible on open blaze.

At the corner point
(Cont. Next Page)

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 200600

PRIMARY CORNER DESCRIPTION Sec. cor. for 5, 6, 7 and 8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground,
with brass cap mkd:

T 22 S R 7 W
S 6 | S 5
S 7 | S 8
1968

from which new bearing trees

A Fir 9" dia., bears N.62°E., 64 lks. dist. mkd. T22S R7W
S5 BT.

A W.Fir 7" dia., bears S.71°W., 84 lks. dist. mkd. T22S
R7W S7 BT.

Deposit the iron rod alongside the iron post.

Tony Hostetter - For: Seneca Jones Timber Co. - 5/2005 -
M147-75

Found - 1968 BLM brass cap, from which
18" fir, face evident BLM tag, bears N.62°E., 64 lks
15" fir, face evident, BT tag (2000), bears N.73°E.,
14.2 ft.
12" fir, face evident, BT tag (2000), bears S.83°W,
15.7 ft.
14" fir, face evident, BT tag (2000), bears N.25°W.,
12.9 ft.

Note - No record of 2000 BTs

Harvey Christensen - For: Seneca Jones Timber Co. - Aug. 2006
- M151-45

Found - 3.25" 1968 BLM brass cap, 0.1 above ground.
48" D.Fir S.52°E., 92.4 ft. 2 ft high stump, partial
blaze.
36" D.Fir S.10°W., 22.4 ft., stump, old obliterated
face.
17" D.Fir N.62°E., 42.2 ft. healed face (blm tag)
15" D.Fir N.80°E., 14.2 ft. healed face (blm tag)
(2000 tag)
13" D.Fir S.63°E., 33.1 ft healed face (blm tag)
(2000 tag)
10" D.Fir S.83°W., 15.7 ft healed face (blm tag)
(2000 tag)
12 D.Fir N.25°W., 12.9 ft. healed face (blm tag)
4.5' stump (CC) (2000 tag)

Set - 6' steel post 0.5' north

continued next page

PRIMARY CORNER DESCRIPTION Sec. Cor. for 5, 6, 7 and 8

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2824, surveyed May 2016/March 2018 - (DCSO records Vol. 59 Page(s) 23885-6)

The cor. of secs. 5, 6, 7, and 8, monumented with an iron post, 2½" dia., firmly set, projecting 3" above ground, with brass cap (properly) mkd. from which the remains of the original bearing trees reported by Peterson in 1968

A sawed decayed fir stump, 48" dia., bears S.52°E., 92.4 ft., with axe marks visible on bark.

A sawed decayed fir stump, 36 ins diam., bears S.16¼°W., 22.4 ft., with axe marks visible over a healed blaze. (Record, S.10°W.)

and the remains of the bearing trees mkd. by Godfrey in 1962

A sawed burnt fir stump, 20" dia., bears N.40°E., 26.4 ft. with axe marks visible.

A burnt decayed fir stump, 14" dia., bears S.70°E., 21.8 ft., no marks visible.

A decayed hemlock stump, size indeterminate, bears N.17°W., 37.6 ft., with no marks visible.

and the remains of a bearing tree mkd. by Peterson

A root hole bears N.62°E., 42.2 ft., alongside of which is a partially uprooted fir trunk, 17" dia., with a healed blaze.

and the remains of the BTs mkd. by person(s) unknown

A fir, 18" dia., bears N.75¼°E., 14.3 ft. with a healed blaze.

A fir, 16" dia., bears S.66½°E., 31.9 ft., with a healed blaze.

A fir, 15" dia bears S.83°W., 15.2 ft., with a double healed blaze.

A sawed fir stump, 12" dia., bears N.26°W., 13.0 ft., with a double healed blaze.

and a new bearing tree

A fir, 4" dia., bears N.53¼°W., 79.8 ft., mkd. X BT.

Each new BT has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center & each monument established or remonumented has a magnet deposited in a white plastic case at the base of the stainless steel post. Alum. Angle iron driven alongside each monument.

NAD 1983 (2011)

Latitude: 43°40'42.07" N. Longitude: 123°33'54.65" W.