

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 200700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 5 & 6; 31 & 32, T21-7

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 2 Page(s) 633)

Set post cor. of secs. 5, 6, 31 and 32; from which
A Cedar 18" dia., bears N.27°E., 75 lks. dist.
A Maple 12" dia., bears N.53°W., 73 lks. dist.
A Fir 16" dia., bears S.67°W., 95 lks. dist.
A Fir 24" dia., bears S.7°E., 61 lks. dist.

GL0 survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #514, dated August 27, 1884 (DCSO records Vol. 2 Page(s) 666)

Could find no evidence or trace of cor. Renewed the same by setting post, 6" dia., 4 ft. long, with marked stone, 12" in ground, mkd. T21S S32 on NE.; R7W S5 on SE.; T22S S6 on SW.; S31 on NW. face, with 5 notches on E. and 1 on W. edges; from which
Cedar 12" dia. bears N.33°W., 16 lks. mkd. T21S R7W S31 BT
Cedar 18" dia. bears N.63°E., 25 lks. mkd. T21S R7W S32 BT
Cedar 20" dia., bears S.43°E., 46 lks. mkd. T22S R7W S5 BT
Cedar 18" dia., S.86°W., 32 lks. mkd. T22S R7W S6 BT

BLM resurvey by Floyd A. Brooks and James E. Jelley, Cadastral Surveyors, under Group #'s 350 and 536, surveyed May/June 1964 (DCSO records Vol. 32 Page(s) 13511)

Point for the sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:
T 21 S R 7 W
S 31 | S 32
S 6 | S 5
T 22 S
1964

from which
A Fir 12" dia., bears N.38½°E., 20 lks. dist. mkd. T21S R7W S32 BT.
A Fir 15" dia., S.73°E., 21 lks. dist. mkd. T22S R7W S5 BT
A Fir 16" dia., bears S.36 3/4°W., 16½ lks. dist. mkd. T22S R7W S6 BT.
A Fir 30" dia., bears N.5°W., 40 lks. dist. mkd. T21S R7W S31 BT.

FD. Ok by T. Hostetter, May 2005 - M147-75

continued next page

PRIMARY CORNER DESCRIPTION Sec. Cor. for 5 & 6; 31 & 32, T21-7

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

Dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2114, surveyed Sept. 2005/Oct. 2006 - (DCSO records Vol. 55 Page(s) 21635)

The cor. of secs. 5, 6, 31, and 32, on the S. bdy. of the Tp., monumented with an iron post, 2½" dia., firmly set, projecting 3" above ground, with brass cap (properly) mkd. from which the remains of the bearing trees mkd. by Brooks and Jelley in 1964

A fir, 18" dia., bears N.63½°E., 12.3 ft., with a healed blaze. (Record, N.38½°E., 13.2 ft.)

A fir, 21" dia., bears S.73°E., 13.9 ft., with a healed blaze.

A decayed fir stump, 16" dia., bears S.36¾°W., 10.9 ft., with a healed blaze.

A fir, 40" dia., bears N.5°W., 26.4 ft., with a healed blaze.

No suitable trees to the SW. available.

A metal fence post is alongside the cor.

Corner is located on the NE. cor. of fir reproduction, edge bears S. and W.

BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor Under Group No. 2500, Surveyed May 2012 - DCSO records BLM Plat 2013-1, T22-7 and Vol. 58 Page(s) 22975

The cor. of secs. 4, 5, 32, and 33, on the N. bdy. of the Tp., perpetuated by Baker, in 2003, monumented with an iron post, 1¾" dia., firmly set, in a collar of stone, projecting 12" above ground, with brass cap (properly) mkd, from which the remains of the original BTs

A decayed fir stump, 60" dia., bears N.19°E., 6.5 ft., with no marks visible. (Record, N.50°E., 4.0 ft.)

A burnt, hollowed cedar snag, size indeterminate, bears S.30°E., 12.4 ft. with no marks visible. (Rec. 14.5 ft)

A sawed, decayed fir stump, 44" dia., bears S.45°W., 28.4 ft., with fragmentary scribe marks visible on an open blaze and a metal cover.

and remains of BTs mkd. by Godfrey, in 1962

A fir, 38" dia., bears N.62°E., 55.8 ft., with a healed blaze. (Record, N.63½°E., 57.4 ft.)

A hemlock, 18" dia., bears S.24°E., 14.5 ft., with a healed blaze. (Record, S.17¾°E.)

A fir, 22" dia., bears S.34°W., 14.5 ft., with a healed blaze.

and a BT mkd. by Baker

A fir, 13" dia., bears N.88½°W., 26.7 ft., with a healed blaze.

continued next page

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 200700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 5 & 6; 31 & 32, T21-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Corner is located on a SE. slope, 63 ft. E. of the top of a spur, slopes S.10°W., and 210 ft. E. of a ravine, drains S.22°E.

Latitude 43°41'35.91"N. Longitude 123°33'51.09"W.
(NAD 1983 (CORSS 96))

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2824, surveyed May 2016/March 2018 - (DCSO records Vol. 59 Page(s) 23896-7)

The cor of secs. 5, 6, 31, and 32, on the N. bdy. of the Tp monumented with an iron post, 2½" dia., firmly set, projecting 3" above ground, with brass cap (properly) mkd. from which the remains of the bearing trees mkd. by Brooks and Jelley in 1964-65, reported by Skeesick in 2012

A fir, 19" dia., bears N.63½°E., 12.3 ft., with a healed blaze.

A fir, 22" dia., bears S.73°E., 13.9 ft., with a healed blaze.

A sawed decayed fir stump, 13" dia., bears S.36¾°W., 10.9 ft., with a healed blaze.

A fir, 43" dia., bears N.5°W., 26.4 ft., with a healed blaze with a cable scar at the base of the tree.

and a bearing tree mkd. by Skeesick

A fir, 5" dia., bears S.74¼°W., 28.6 ft., with a double healed blaze.