

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 240600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 5 and 8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 152 survey dated June 3, 1871 (DCSO records Vol. 4 Page(s) 1526)

Set ¼ sec. post, from which
A Fir 10" dia., bears N.28°E., 7 lks. dist.
A Fir 10" dia., bears S.80°W., 12 lks. dist.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - V. Tracy and M. Stone, crew - July 17, 1962 - C.S. File 52/14-95

Found - Fir now 17", N.28°E., 4.6 ft. chopped open and found good scribing "S" on old face.
Fir, now 21", S.80°W., 7.9 ft. shows good scars.
Found bark scribing "B". I reblaze and scribe this tree "¼ S CS BT"

Set Brass cap at cor. mkd: County Surveyors Office
T 22 S R 7 W
¼ $\frac{S}{S}$ $\frac{5}{8}$
1962

New BT - 17" D.Fir N.37°E., 7.1 ft. mkd. ¼ S5 CS BT.
Corner lies directly on top of spur running N.50°E., approx. 200 ft. (elev) above creek bottom to East.

Harvey Christensen - For: Seneca Jones Timber Co. - Aug. 2006 - M151-45

Found - 2.5" 1962 DCSO BC, 1.0 above ground, leaning East, tied base of pipe.
16" D.Fir N.28°E., 4.6 ft. (Face measure), 3' high stump, disturbed, pushed NE, scribing visible, tags state 5,7 ft (Haines) & 6 ft approx (blm)
20" D. Fir, S.80°W., 7.9 ft. (Face measure) 3' stump, scribing visible

New - 9" D.Fir, N.60°W., 7.4 ft blazed & scribed "¼ S5 BT"
12" D.Fir N.48°E. 19.6 ft blazed & scribed "¼ S5 BT"
10" W.Fir S.48°W. 12.2 ft blazed & scribed "¼ S8 BT"
11" W.Fir S.64°E. 18.9 ft blazed & scribed "¼ S8 BT"

Note - Corner falls on ridge