

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 300200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 28, 29, 32 and 33

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1507)

-----  
Set post cor. of secs. 28, 29, 32 and 33, from which  
A B.Oak 24" dia., bears N.50°W., 228 lks. dist.  
A B.Oak 24" dia., bears S.83°W., 390 lks. dist.  
A W.Oak 24" dia., bears N.68°E., 195 lks. dist.  
No tree convenient in sec. 33.

J.W. Cole, Deputy - L.H. Smick; Wm. Levins; Felix Hudson - Feb. 1921 - Vol. 3 Page 155 and Field Book 50 Page 18

-----  
Renewed this corner from two original BTs. The tree S.83°W. checks for distance and about 2° off for bearing. Tree N.50°W checks both for bearing and distance.  
I set a rock 6" x 6" x 12". Also an Oak post 4" x 4" x 40" and mark new trees:  
An Oak 12" dia. S.32°W., 18.2 ft.  
An Oak 12" dia. N.21°45'W., 55.4 ft.

Wilford N. Haines - For: Woolley Logging Co. and E.G. Whipple Mill - April 1961 - (Print only file, work not completed) C.S. File 51/191 and M 38-69

-----  
Found - Rock and BTs by Cain, 1921. Rock is leaning against fence corner post.  
Set 1" x 1" x 36" T-Iron.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - V. Tracy & C Putnam, crew - April/May 1962 - C.S. File 52/14-103

-----  
Found - T-Iron set by Haines in 1961.  
Both BTs mkd. by Cole in 1921.  
W.Oak now 33" S.32°W., 16.2 ft., shows good scar.  
W.Oak now 34" N.21¼°W., 55.4 ft., shows good scar  
Rock set by Cole out of ground, probably dug out when fence built.  
Blaze and scribe one new tree:  
29" W.Oak N.17°E., 72.0 ft. mkd. T22S R7W S28 CSBT.

Fd. T-Iron, July 1981, R.Dolan, M 88-27  
Fd. OK, Sept. 1990, M 111-26

continued next page

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 300200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 28, 29, 32 and 33

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Douglas Co. Surveyors Office - Randall W. Smith, Deputy -  
Stephen J. Flause - 10/24/2001 and 5/2/2002 - C.S. File  
66/32-29

-----

10/24/2001

Found - 1961 Haines T iron, protrudes 15" out of ground at  
old 4-way fence corner. 1921 stone not found.  
12" now 40" dia., W.Oak, no blaze visible bears  
S.28°W., 16.2 ft. (1962 rec. S.32°W., 16.2 ft.)  
1921 BT  
29" now down 19" dia., Oak agrees well with rec.  
N.17°E., 72.0 ft. no marks visible does not look  
as if it could of been 29" dia. 1962 BT.?  
1921 NW BT now gone.  
NE OBT now gone  
NW OBT not standing, area logged in past would fall  
in solid patch of blackberries, stump not looked  
for.  
SW OBT gone.  
Compass decl. 17½°E.

5/02/2002

Set - 2 3/8" dia., brass cap on a 1 3/8" O.D. by 32" long  
iron pipe at position of fd. "T" iron, protrudes  
8" above ground. "T" measures 36" long, set along  
North edge of BC/IP protrudes 7" out of ground.

DOUGLAS COUNTY SURVEYORS OFFICE

T 22 S

R 7 W

S 29 | S 28

S 32 | S 33

2002

New - 14" dia., D.Fir double blazed & scribed "T22S R7W  
S33 CS BT" bears S.12½°E., 31.7 ft.  
30" dia., D.Fir double blazed & scribed "T22S R7W  
S28 CS BT" bears N.55½°E., 160.7 ft.  
No suitable trees northwest.