

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 28 and 29

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1508)

Set ¼ sec. post, from which
A W.Oak 20" dia., bears N.58°W., 198 lks. dist.
A W.Oak 10" dia., bears N.45°E., 147 lks. dist.

J.W. Cole, Deputy - Wit: L.H. Smick; Wm. Levins; Felix Hudson - Feb. 1921 - Vol. 3 Page 155 and Field book 50 Pg. 18

Renewed this cor. from the original BT which are alive and standing, chopped out blaze on tree N.45°E. which shows scribe marks.
Set a 4" x 4" x 40" Oak post.

Wilford N. Haines - For: Woolley Logging Co. and E.G. Whipple Mill - April 1961 - (print only filed, work not completed) C.S. File 51/191 and M 38-69

Found - Two orig. BTs:
20" Oak N.58°W., 198 lks., a stump.
10" Oak N.45°E., 145 lks., rescribed.
Set 1" x 1" x 36" T. Iron.
Scribed -18" Fir S.66°W., 144.4 ft.

Fd. OK, April 1982, L. Roberts, M 91-76
Fd. OK, Sept. 1990, M 111-26
Fd. OK, May 1997, D. Baker, M 127-15

BLM dependent resurvey by Bryan S. Seibold, Cadastral Surveyor, under Group #1797, surveyed April/June 1996 - (DCSO records Vol. 52 Page(s) 20171-2)

The ¼ sec. cor. of secs. 28 & 29, perpetuated by Cole, Deputy County Surveyor, in 1921, further perpetuated by Haines, in 1961, from original evidence no longer in existence; monumented with a "T" iron, firmly set, projecting 1" above ground, from which the remains of a BT mkd. by Haines:

A fir, 34" diam., bears S.66½°W., 218 lks., with healed double blaze.

At the corner point

Set a stainless steel post, 28" long, 2½" diam., 27" in the ground, directly over the "T" iron, with brass cap mkd.

T 22 S R 7 W

1/4

S 29 S 28

1996

continued next page

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 300240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 28 and 29

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

and a new bearing tree

A fir, 10" diam., bears S.77°E., 186 lks., mkd. ¼ S28 BT.
Deposit a magnet in a white plastic case at the base of the
stainless steel post.

Corner is located in a 5 strand electric fence, extending N.
and S.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy -
Stephen J. Flause - 5/22/2002 - C.S. File 66/34-3

Found - 1996 BLM brass cap/iron pipe flush w/ground in N-S
fence line.

18" now 36" dia., D.Fir with a fully healed double
blaze bears S.66½°W., 143.9 ft. (1961)

10" now 17" dia., D.Fir with a fully healed single
blaze, bears S.77°W., 122.8 ft. (1996)

New - 20" dia., D.Fir double blazed & scribed "¼ S29 CS
BT" bears N.16°W., 22.0 ft.

6" dia., D.Fir double blazed & scribed "¼ S28 CS BT"
bears S.21°E., 36.5 ft.

Compass decl. 17½°E.