

PRIMARY CORNER DESCRIPTION Sec. Cor. for 20, 21, 28 and 29

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1508)

-----  
Set post cor. of sec. 20, 21, 28 and 29, from which  
A Fir 36" dia., bears N.40°W., 192 lks. dist.  
A Fir 30" dia., bears S.52°W., 102 lks. dist.  
A Fir 30" dia., bears S.67°E., 202 lks. dist.  
Mill's house bears N.45°E.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - V. Tracy and C. Putnam, crew - March 1962 - C.S. File 52/14-126

-----  
Found - 2" Iron pipe.  
Fir tree, 60" S.52°W., 67.3 ft. Had been opened previously and old face visible. Good reverse scribing "B" found on chip lying in notch.  
Badly rotted Fir stump N.40°W., 126.7 ft. No scribing found.  
Old Fir stump 48", S.67°E., 133.3 ft. Did not chop open.

Did not set Brass cap

New BTs -15" D.Fir S.27°E., 40.3 ft. mkd. T22S R7W S28 CS BT  
29" D.Fir S.4°W., 30.6 ft. mkd. T22S R7W S29 CS BT.  
23" D.Fir N.12½°W., 116.8 ft. mkd. T22S R7W S20 CSBT  
20" D.Fir N.54°E., 110.9 ft. mkd. T22S R7W S21 CSBT.

Found OK, May 1989, D. Baker, M 101-55  
Found OK, May 1997, D. Barker, M 127-15

BLM dependent resurvey by Bryan S. Seibold, Cadastral Surveyor, under Group #1797, surveyed April/June 1996 - (DCSO records Vol. 52 Page(s) 20163-4)

-----  
The cor. of secs. 20, 21, 28 & 29, perpetuated by Godfrey, in 1962; monumented with an iron pipe, 2½" diam., firmly set, projecting 9" above ground, from which the remains of an original bearing tree:

A roothole, bears S.52°W., 102 lks., with uprooted trunk, 60" diam., alongside, no marks visible.  
and the remains of bearing trees mkd. by Godfrey  
A sawed fir stump, 31" diam., bears N.54 3/4°E., 167 lks., with healed blaze.  
A sawed fir stump, 27" diam., bears S.27°E., 61 lks., with healed blaze.

A fir, 36" diam., bears S.3½°W., 46 lks., with healed blaze.

A sawed fir stump, 39" diam., bears N.12¼°W., 176 lks., with healed double blaze.

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 300300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 20, 21, 28 and 29

| Alias | Description |
|-------|-------------|
|       |             |
|       |             |
|       |             |
|       |             |

At the corner point

Set a stainless steel post, 28" long, 2½" diam., 27" in the ground, with brass cap mkd.

|        |       |
|--------|-------|
| T 22 S | R 7 W |
| S 20   | S 21  |
| S 29   | S 28  |
| 1996   |       |

from which new bearing trees

A fir, 15" diam., bears N.85 3/4°E., 196 lks., mkd. T22S R7W S21 BT.

A fir, 8" diam., bears S.78 3/4°E., 196 lks., mkd. T22S R7W S28 BT.

A fir, 22" diam., bears N.16 3/4°W., 98 lks., mkd. T22S R7W S20 BT.

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Buried 2½ in. diam. iron pipe alongside stainless steel post and drove a metal fence post S., 0.02 chs. dist. from the corner.

Fd. Ok by K. DeGroot, 12/2006 - M146-51