

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 300340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 20 and 21

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1509)

-----  
Set ¼ sec. post, deposited charred stake, raised mound with trench and pits, as per instructions.

Floyd Cole, Deputy - Wit: S. Brown; W. Frost - July 5, 1913 -Vol. 2 Pages 254; Field Book 39 Pg. 12 (and "old" renewal book, pg. 23)

-----  
Set a rock 8" x 12" x 30" on end.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - V. Tracy and C. Putnam, crew - March 1962 - C.S. File 52/14-127

-----  
Found - Rock 8" x 12" x 30" set by Cole in 1913. No markings found. Corner lies on open grass slope with no other rocks in the vicinity. It checks out directly South from cor. 16-17-20-21 and also fits orig. call from top of ridge. Rock set 24" in ground.

Set brass cap alongside rock mkd: County Surveyors Office  
T22S R7W ¼ S20|S21  
1962

New BTs -36" W.Oak N.27°E., 203.6 ft. mkd. ¼ S21 CS BT.

24" W.Oak S.17°W., 278.6 ft. mkd. ¼ S20 CS BT.

Corner on open, grassy, South slope, 365 ft. South of ridge top.

Fd. OK, May 1989, D. Baker, M 101-55

Fd. Ok by K. DeGroot, 12/2006 - M146-51