

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 300540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 8 and 9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by W.H. Byars, Deputy Surveyor under contract # 152 survey dated June 3, 1871 (DCSO records Vol. 4 Page(s) 1525)

Set ¼ sec. post, from which
A Fir 40" dia., bears N.38°E., 33 lks. dist.
A Fir 48" dia., bears N.20°W., 17 lks. dist.

Wilford N. Haines, #239 - For: Woolley Logging Co. - Dec.1963
M 27-16

Set 1" x 1" x 36" T Iron, from which, scribed
6" W.Fir S.5°W., 2.9 ft.
6" W.Fir N.88°E., 21.8 ft.

Wilford N. Haines, #239 - For: May 30, 1965 - C.S. File
51/309-2

Found T Iron in place. Both BTs gone.
New BTs -8" D.Fir N.71°W., 40.0 ft.
5" W.Fir N.15°E., 48.9 ft.

Troy Rambo - For: Seneca Jones Timber - Mar. 2004 - M144-19

Found - "T" iron per M27-60
Did not find the rec. BTs.
New - Scribed ¼ S8 BT" on 9" DF - bears N.11°W., 11.0 ft.
Scribed ¼ S8 BT" on 10" DF - bears S.66°W., 11.5 ft
Scribed ¼ S9 BT" on 12" DF - bears S.76°E., 18.3 ft
Scribed ¼ S9 BT" on 11" DF - bears S.40°E., 13.5 ft

Harvey Christensen - For: Seneca Jones Timber Co. - Aug. 2006
- M151-45

Found - 1" "T" rod w/o brass cap (Haines) 0.8 ft above
grade.
16" W.Fir N.15°E., 48.9 ft, healed face, Haines
9" D.Fir N71°W., 40.0 ft. 1" stump scribing visible,
Haines
CS M144-19 (Rambo) BTs were also found as described.
Haines proportioned corner is N.28°51'E., 9.6' from mid point
& 4.5" east of the section line. Upon searching for the
original corner a 48' D.Fir 3' stump was located with partial
face & accepted for evidence of the original NE BT. A small
depression was found at the location of the NW BT position.
Distance to creek CL was within acceptable limits (2.1 ch)

continued next page

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 300540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 8 and 9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Set - A 2.5" aluminum cap was set on a 5/8"x30" rebar stamped "NTCI LS 2603" record bearing & distance from the face of said fd stump (S.38°W., 21.8 ft) Additional bearing trees added as follows, not suitable trees available in clear cut to SW.
14" D.Fir north, 22.7 ft. blazed & scribed "¼ S8 BT"
10" D.Fir N.26°E. 19.8 ft blazed & scribed "¼ S9 BT"
17" W.Fir S.15°E. 32.6 ft blazed & scribed "¼ S9 BT"
Note - Corner falls 40' north of road, 140' (2.1 ch.)(2.5 ch record) north of CL creek.

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2892, surveyed April/May 2018- (DCSO records Vol. 59 Page 23746-7)

The ¼ sec. cor. of secs. 8 and 9, perpetuated by Christensen in 2006; monumented with an iron rod, 5/8" dia., firmly set, projecting 4" above ground, with an aluminum cap mkd.

NTC1
T22S R7W
S 8 | S 9
¼ 2006
PLS 2603

from which the remains of an original bearing tree
A sawed, decayed fir stump, 41" dia., bears N.38°E., 21.8 ft., with a healed blaze.

and the bearing trees mkd. by Christensen

A fir, 18" dia., bears N.27¾°E., 20.2 ft., with a healed blaze.

A fir, 21" dia., bears S.17°E., 33.0 ft., with a healed blaze.

A fir, 18" dia., bears N.4¾°W., 22.6 ft., with a healed blaze.

At the corner point

Set a stainless steel post, 28" long, 2½" dia., 25" in the ground, directly over the inverted iron rod, 30" long, with brass cap mkd.

T 22 S R 7 W

¼
S 8 | S 9

2018

From this cor., a point erroneously reestablished as the ¼ sec. cor. of secs. 8 and 9, by Haines in 1963, perpetuated by Haines in 1965; subsequently perpetuated by Rambo in 2004; subsequently rejected by Christensen in 2006, and was not utilized in the course of this survey; bears N.4°11'28"E., 53.92 ft.; monumented with a "T" shaped iron rod, ¾" dia., firmly set, projecting 9" above ground, from which the remains of the BTs mkd. by Haines in 1965 cont. next pg

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 300540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 8 and 9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A sawed, decayed fir stump, 13" dia., bears N.15¼°E., 50.3 ft., with a healed blaze.
A fir, 16" dia., bears N.71¼°W., 40.0 ft., with a healed blaze.
and the bearing trees mkd. by Rambo
A fir, 15" dia., bears S.77½°E., 18.3 ft., with a healed blaze.
A fir, 15" dia., bears S.44¼°E., 13.1 ft., with a healed blaze.
A fir, 14" dia., bears S.64¼°W., 11.5 ft., with a healed blaze.
A fir, 12" dia., bears N.12¼°W., 10.5 ft., with a healed blaze.