TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 338600

PRIMARY CORNER DESCRIPTION S. 1/4 Cor. for Sec. 4 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Carl S. Nicklin, Deputy Surveyor, under joint contract # 664 dated May 23, 1896 (DCSO records Vol. 4 Page(s) 1547-48)

Set a Fir post 3 ft. long, 4" sq., 24" in the ground for ¼ sec. cor., mkd. ¼ S on N. face; from which
A Fir 30" dia., bears N.75°E., 13 lks. dist. mkd. ¼ S BT
A Fir 30" dia., bears S.67½°W., 58 lks. dist. mkd. ¼ S BT
This cor. is on the point of spur, sloping W.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - V. Tracy and C. Putnam, crew - March 1962 - C.S. File 52/14-113

Found - Rotted W.Fir snag, S.67½°W., 38.3 ft. Opened and found good scribing "B.T."
54" D.Fir stump, N.75°E., 8.6 ft. Did not cut open
Set Brass cap at cor. mkd: County Surveyors Office
T 22 S R 7 W
¼ S 4 / S 9
1962
New BTs -16" D.Fir N.56°W., 84.2 ft. mkd. ¼ S4 CS BT.
60" D.Fir S.3°W., 30.0 ft. mkd. ¼ S9 CS BT.
4" x 4" sq. stake, 2 ft. above ground, painted white and mkd: "S¼ S4" on North face, bears S.48°W., 4.2 ft.

NOTE: THIS IS THE SOUTH 1/4 CORNER FOR SEC. 4 ONLY

Wilford N. Haines, #239 - Nov. 30, 1965 - C.S. File 51/309-2

Found - I.P. with brass cap set by County, 1962.
Stump, S.3°W., 30.0 ft., some scribing still on stump, rescribed on NE. face.
Orig. stump, NE, still there but no scribe.
New BT - 5" Fir N.12°E., 186.0 ft.

Cor. OK, Feb. 1966

David Edwards - For Seneca Jones Timber Co- 11/2004 - M145-72

Found - Brass cap
16" Fir N.12°E., 186.0' healed blaze.
22" Fir with BLM tag N.68°E., 30.0' no blaze. (no record)