

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. for Sec. 28

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

Wilford N. Haines, #239 - For: Whipple and Woolley - Filed Dec. 8, 1969 - C.S. File 51/191 and M 38-69

Set T Iron, 1" x 1" x 36" and scribed
6" Fir N.25°W., 82.6 ft.
10" Fir S.46°E., 121.1 ft.

BLM dependent resurvey by Bryan S. Seibold, Cadastral Surveyor, under Group #1797, surveyed April/June 1996 - (DCSO records Vol. 52 Page(s) 20169-70)

The center ¼ sec. cor. of sec. 28, established by Haines, in 1961, and is accepted as the corner; monumented with a "T" iron, firmly set, projecting 15" above a mound of stone, 3 ft. base, 2 ft. high, from which bearing trees mkd. by Haines:

A fir, 27" diam., bears S.52 3/4°E., 183 lks., with healed double blaze.

A fir, 17" diam., bears N.23°W., 125 lks., with healed double blaze.

At the corner point

Set a stainless steel post, 28" long, 2½" diam., 6" in the ground, directly over the "T" iron, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 22 S R 7 W

C 1/4 S 28

1996

and new bearing trees

A fir, 12" diam., bears S.78 3/4°E., 46 lks., mkd. C ¼ S28 BT.

A fir, 10" diam., bears S.20°E., 37½ lks., mkd. C ¼ S28 BT.

Deposit a magnet in a white plastic case at the base of the stainless steel post.