

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 340300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 21 & 28

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1511)

Set ¼ sec. post, deposited charred stake, raised mound with trench & pits as per instructions.

BLM dependent resurvey by Bryan S. Seibold, Cadastral Surveyor, under Group #1797, surveyed April/June 1996 - (DCSO records Vol. 52 Page(s) 20163)

Point for the ¼ sec. cor. of secs. 21 & 28, at proportionate dist., there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 42" in the ground, with brass cap mkd.

T 22 S R 7 W
S 21
1/4 _____
S 28
1996

from which

An oak, 21" diam., bears S.78¼°E., 556 lks., mkd. ¼ S28 BT

An ash, 9" diam., bears N.60°W., 430 lks., mkd. ¼ S21 BT.

Deposit a magnet in a white plastic case at the base and set a steel fence post alongside the stainless steel post.

Corner is located in a large open pasture.