

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 9 and 16

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars, Deputy Surveyor under contract # 152 survey dated June 3, 1871 (DCSO records Vol. 4 Page(s) 1524)

-----  
Set ¼ sec. post, from which  
A Maple 10" dia., bears N.42°W., 12 lks. dist.  
A Fir 60" dia., bears S.72°E., 30 lks. dist.

Les Roberts - For: International Paper Co. - May 24, 1989 - C.S. File 63/91 and M 108-22

-----  
(No evidence found of original corner)  
Set 3/4" x 36" alum. rod with 3¼" alum. cap by single proportionate measure. Buried purple magnetic marker under 36" alm. rod. Set alum. post, with land survey monument sign bolted to, beside alum. cap.  
New BTs -33" Fir bears S.02°W., 29.1 ft. (scribed/ painted red)  
48" Fir stump bears N.34°W., 84.0 ft. (scribed/ painted red.)  
Corner lies on South slope at the edge on a new clearcut unit

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2892, surveyed April/May 2018- (DCSO records Vol. 59 Page 23743-4)

-----  
The ¼ sec. cor of secs 9 & 16, reestablished by proportionate measurement by Roberts in 1989. There is no remaining evidence of the orig. cor., therefore this point is accepted as a careful & faithful reestablishment of the cor monumented with an aluminum rod, 3/4" dia., firmly set, projecting 10" above ground, with an aluminum cap (properly) mkd. from which the remains of the BTs mkd. by Roberts  
A sawed fir stump, 36" dia., bears S.0¼°W., 29.4 ft., with a healed blaze.  
A sawed decayed fir stump, 52" dia., bears N.35¼°W., 81.2 ft., with scribe marks N¼ S16 BT visible on open blaze.  
At the corner point  
Set a stainless steel post, 28" long, 2½" dia., 26" in the ground, directly over the inverted aluminum rod, 36" long, with brass cap mkd: T 22 S R 7 W  
¼  $\frac{S \ 9}{S \ 16}$   
2018  
from which  
A fir, 12" dia., bears S.18¼°W., 12.0 ft., mkd. ¼ S16 BT  
A fir, 9" dia., bears N.84¼°W., 13.5 ft., mkd. ¼ S9 BT.

Continued next page

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 340500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 9 and 16

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Each new BT has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center & each monument established or remonumented has a magnet deposited in a white plastic case at the base of the stainless steel post. Alum. Angle iron driven alongside.