

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 33 and 34

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by W.H. Byars, Deputy Surveyor under contract # 152 survey dated June 3, 1871 (DCSO records Vol. 4 Page(s) 1529)

-----

Set ¼ sec. post.  
No tree, threw up mound as per instructions.

---

Wilford N. Haines, #239 - For: Whipple and Woolley - April 1961 - (filed 12/8/69) C.S. File 51/191 and M 38-69

-----

Set 1" x 1" x 36" T Iron.  
Scribed - 11" W.Fir N.49°W., 171.3 ft.  
12" W.Oak S.27°E., 359.1 ft.

---

Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 5/30/2002 - C.S. File 66/34-5

-----

Found - 1961 bent Haines "T" iron protrudes 4" out of ground  
11" now 33" dia., 1½ ft. high D.Fir stump we open & find good scribe mark & blaze, bears N.49°W., 171.3 ft. (1961)  
12" now 26" dia., 1 ft. high W.Oak stump, no mark visible, bears S.27°E., 359.1 ft. (1961)

New - 29" dia., D.Fir single blazed & scribed "¼ S33 CS BT" bears S.78¼°W., 185.7 ft.  
22" dia., D.Fir double blazed & scribed "¼ S33 CS BT" bears S.31¾°W., 482.0 ft.  
22" dia., W.Oak double blazed & scribed "¼ S34 CS BT" bears S.16¾°E., 411.8 ft.  
32" dia., W.Fir double blazed & scribed "¼ S34 CS BT" bears S.33½°E., 406.6 ft.  
Compass decl. 17½°E.

Set - 5/8" by 60" long iron rod with DCSO alum. cap stamped: ¼  
33|34  
2002 at plumb position of  
Haines "T" iron protrudes 8" above ground.  
Metal wit. post & sign set 1 ft. north.

Note - Corner lies in open field no reasonable trees to the north.