

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 400200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 27, 28, 33 and 34

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

GLO survey by W.H. Byars, Deputy Surveyor under contract # 152 survey dated June 3, 1871 (DCSO records Vol. 4 Page(s) 1528)

Set post cor. to secs. 27, 28, 33 and 34, from which
A Fir 36" dia., bears N.30°E., 24 lks. dist.
A Fir 5" dia., bears S.30°E., 25 lks. dist.
A Maple 5" dia., bears S.85°W., 10 lks. dist.
A Maple 4" dia., bears N.62°W., 54 lks. dist.

Wilford N. Haines, #239 - For: Woolley Logging Co. and Whipple Mill - April 1961 - (Print only filed, work not completed) C.S. File 51/191 and M 38-69

Found - 4" Fir S.30°E., 25 lks., now 36".
36" Fir N.30°E., 24 lks., now down.
4" Maple N.62°W., 54 lks., now down.
5" Maple S.85°W., 10 lks., no scribe seen.
Set 1" x 1" x 36" T Iron
Scribed- 10" Fir S.20°W., 52.0 ft.
24" Fir N.31°W., 19.8 ft.
10" Fir N.71°E., 19.7 ft.

David Edwards - Crew: B. Miller & E. Sprinkle - 1/5/2015 - C.S. File 65/87-1

Found - 1984 B.L.M. brass cap good condition.
30" dia. Fir stump bears S.28°W., 35.6'.
13" dia. Fir with healed blaze bears N.53°W., 36.3'.
Rock outcrop not searched for.
New - A 24" diam. Fir bears N.84°E., 6.9 feet scribed "¼ S27 BT"
No suitable trees available in Sec. 34.
A 6 foot steel post is set 2 ft West.
15°E dec.