

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 27 and 28

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 152 survey dated June 3, 1871 (DCSO records Vol. 4 Page(s) 1528)

-----  
Set ¼ sec. post, from which  
A Fir 48" dia., bears West, 29 lks. dist.  
A Maple 6" dia., bears East, 44 lks. dist.

Wilford N. Haines, #239 - For: Woolley Logging and Whipple Mill - April 1961 - (Print only file, work not completed) C.S. File 51/191 and M 38-69

-----  
Found - 48" Fir, West 29 lks.  
Set 1" x 1" x 36" T Iron  
Scribe - 5" Fir N.79°26'W., 57.3 ft.  
16" Fir S.8°31'E., 125.3 ft. (on top of ridge)

BLM dependent resurvey by Bryan S. Seibold, Cadastral Surveyor, under Group #1797, surveyed April/June 1996 - (DCSO records Vol. 52 Page(s) 20160)

-----  
Beginning at the ¼ sec. cor. of secs. 27 & 28, perpetuated by Haines, in 1961, from original evidence no longer in existence; monumented with a "T" iron, firmly set, projecting 10" above ground, from which the remains of bearing tree mkd. by Haines:

- A sawed fir stump, 26" diam., bears S.7¼°E., 192 lks., no scar or marks visible.
- A fir, 20" diam., bears N.79°W., 86 lks., with healed double blaze.

At the corner point  
Set a stainless steel post, 28" long, 2½" diam., 26" in the ground directly over the "T" iron, with brass cap mkd.

T 22 S R 7 W  
1/4  
S 28 S 27  
1996

and a new bearing tree  
A fir, 20" diam., bears S.41½°E., 42½ lks., mkd. ¼ S27 BT.  
Deposit a magnet in a white plastic case at the base of the stainless steel post.