

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 400300

PRIMARY CORNER DESCRIPTION Sec Cor for 21, 22, 27 and 28

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCS0 records Vol. 4 Page(s) 1511)

-----  
Set post cor. of secs. 21, 22, 27 and 28, from which  
A Fir 12" dia., bears N.10°W., 13 lks. dist.  
A Fir 8" dia., bears N.27°E., 25 lks. dist.  
A Fir 14" dia., bears S.35°E., 116 lks. dist.  
A Dogwood 6" dia., bears S.59°W., 45 lks. dist.

Wilford N. Haines - For: Woolley Logging Co. and E.G. Whipple Mill - April 1961 - (print only filed, work not completed) C.S. File 51/191 and M 38-69

-----  
Found Scribed stake and 3 original Fir BTs.  
Set 1" x 1" x 36" T Iron by stake.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - V. Tracy and C. Putnam, crew - March 1962 - C.S. File 52/14-115

-----  
Found - Haines T Iron  
39" D.Fir N.10°W., 8.6 ft. Chopped open and found good scribing "W" on old face.  
40" D.Fir N.27°E., 16.5 ft. shows good scar.  
58" D.Fir S.35°E., 76.6 ft. shows good scar.  
No trace of Dogwood BT.

Did Not Set Brass Cap.

New BTs - 39" Fir N.10°W., 8.6 ft. mkd. T22S R7W S21 CSBT.  
40" Fir N.27°E., 16.5 ft. mkd. T22S R7W S22 CSBT  
7" D.Fir S.2°W., 21.5 ft. mkd. T22S R7W S28 CSBT  
6" D.Fir S.63°E., 26.2 ft. mkd. S27 CS BT.

Corner is in E & W fence line, on a small bench approx. 300 ft. East of ridge top.

Fd. OK, March 1998 by G. Riley - M 128-33

BLM dependent resurvey by Bryan S. Seibold, Cadastral Surveyor, under Group #1797, surveyed April/June 1996 - (DCS0 records Vol. 52 Page(s) 20161-2)

-----  
The cor. of secs. 21, 22, 27 & 28, perpetuated by Haines, in 1961, further perpetuated by Godfrey, in 1962; monumented with a "T" iron, firmly set, projecting 18" above ground, from which the remains of original bearing trees:

A fir, 43" diam., bears N.27°E., 25 lks., with healed double blaze, this tree was remarked by Godfrey.

A roothole, bears S.35°E., 116 lks., with uprooted trunk, size indeterminate, alongside, no marks visible.

continued next page

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 400300

PRIMARY CORNER DESCRIPTION Sec Cor for 21, 22, 27 and 28

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

A fir, 41" diam., bears N.10°W., 13 lks., with healed double blaze, this tree was remarked by Godfrey and bearing trees mkd. by Godfrey

A fir, 9" diam., bears S.62 3/4°E., 39 1/2 lks., with healed double blaze.

A fir, 10" diam., bears S.3 1/2°W., 32 1/2 lks., with healed double blaze.

At the corner point

Set a stainless steel post, 28" long, 2 1/2" diam., 26" in the ground directly over the "T" iron, with brass cap mkd.

T 22 S	R 7 W
S 21	S 22
S 28	S 27

1996

Deposit a magnet in a white plastic case at the base of the stainless steel post.

From this point, the Douglas County Surveyor's Office horizontal control station "HANCOCK," at latitude 43°38' 43.750"N., longitude 123°31'25.981"W. (NAD 1927), bears N.3°04'39"E., 55.578 chs. (mean bearing & sea level); monumented with a brass disk, firmly set in an 8" cylinder of concrete, flush, with top mkd. DOUGLAS CO. SURVEYORS OFFICE HANCOCK 1982.

Found OK by C. Sweeden, April 2004 - M144-40

Ken Hoffine - For: Juniper Timber Co. - June 2006 - M151-722

-----  
Found - 1996 BLM brass cap at ground level.  
43" D.Fir bears N.16 1/4°W., 8.5 ft (rec N.10°W, 8.6 ft) healed face  
43" D.Fir bears N.13 1/4°E., 16.0 ft (rec N.27°E., 16.5 ft) healed face  
9" D.Fir bears S.63 1/4°E, 26.1 ft (rec S.62 3/4°E, 26.07 ft) healed face and BLM tag  
10" D.Fir bears S.3°W., 21.3 ft (rec S.3 1/2°W, 21.45 ft) healed face and BLM tag  
Corner sits on south facing slope old fence line runs approximately east-west from corner.

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2824, surveyed May 2016/March 2018 - (DCSO records Vol. 59 Page(s) 23894-5)

-----  
The cor. of secs. 21, 22, 27, and 28, monumented with an iron post, 2 1/2" dia., firmly set, projecting, 2" above ground, with brass cap (properly) mkd.

Continued next page

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 400300

PRIMARY CORNER DESCRIPTION Sec Cor for 21, 22, 27 and 28

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

from which the remains of the original bearing trees reported by Seibold in 1996  
A sawed fir stump, 44" dia., bears N.27°E., 16.5 ft., with a healed blaze.  
A sawed fir stump, 44" dia., bears N.10°W., 8.6 ft., with a healed blaze.  
and the remains of the bearing trees mkd. by Godfrey in 1962  
A fir snag, 9" dia., bears S.62¾°E., 26.1 ft. with a healed double blaze.  
A fir snag, 10" dia bears S.3½° W., 21.5 ft., with a healed double blaze.  
and new accessories  
An iron rod, 30" long, 5/8" dia., driven 28" in the ground for a reference monument, bears N.47°43'39"E, 6 00 ft. with an aluminum cap mkd. RM T22S R7W S22 6.00 FT TO COR 2016, and an arrow pointing to the cor  
A fir, 8" dia., bears S.59½°E., 40.2 ft., mkd. T22S R7W S27 BT.  
An iron rod, 30" long, 5/8" dia., driven 29" in the ground for a reference monument bears S.38°17'21"W, 5.00 ft., with an aluminum cap mkd. RM T22S R7W S28 5.00 FT TO COR 2016, and an arrow pointing to the cor  
An iron rod, 30" long, 5/8" dia., driven 29" in the ground for a reference monument bears N.63°50'43"W, 10.00 ft, with an aluminum cap mkd. RM T22S R7W S21 10.00 FT TO COR 2016, and an arrow pointing to the cor