

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 400440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 15 and 16

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars, Deputy Surveyor under contract # 152 survey dated June 3, 1871 (DCSO records Vol. 4 Page(s) 1521)

-----  
Set 1/4 sec. post, from which  
A Fir 8" dia., bears N.60°E., 10 lks. dist.  
A Fir 24" dia., bears N.38°W., 35 lks. dist.

BLM resurvey by John M. Jelley and Donald Beck, Cadastral Surveyors, under Group #590, surveyed July/Aug. 1965 (DCSO records Vol. 33 Page(s) 13962)

-----  
The 1/4 sec. cor. of secs. 15 and 16, determined at record bearing & distance from the remaining original bearing tree:  
A dead Fir 35" dia., bears N.38°W., 35 lks. with scribe marks 1/4 S C S16 visible on bark blaze.

At the corner point  
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:  
T 22 S R 7 W  
1/4  
S 16 | S 15  
1965

from which a new bearing tree  
A Fir 21" dia., bears N.68°E., 55 lks. mkd. 1/4 S15 BT.

Fd. OK, May 5, 1989, L. Roberts, C.S. File 63/91 and M 108-22

Kent Inman - For: Seneca Jones Timber Co. - March 19, 2010 - M160-64

-----  
Found - 3 3/4" brass cap on a 2 1/2" iron post. Up 1" (properly mkd) BLM 1965  
34" D.Fir. with a healed face and BLM BT tags, bears N.68°E., 36.4'  
D.fir snag. size indeterminate. bears N.38°W., 23.1'. Found slabs of bark on the ground. one with a BLM BT tag, the other with scribing 1/4 visible. The bark slabs were placed on the east side of the snag.  
New - Set a 5/8"x30" iron rod with an orange plastic cap marked "INMAN 60050 LS" bears N.39°W., 20.8'  
11" D.Fir bears S.67°E., 37.2' scribed 1/4 S15 BT.  
23" D.Fir bears S.1°E., 32.6' scribed 1/4 S15 BT.

continued next page

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 400440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 15 and 16

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2824, surveyed May 2016/March 2018 - (DCSO records Vol. 59 Page(s) 23897-8)

-----  
The ¼ sec. cor. of secs. 15 and 16, perpetuated by Inman, in 2010 monumented with an iron post, 2½" dia. firmly set, projecting 5" above ground, with brass cap (properly) mkd. from which the remains of an original bearing tree reported by Jelley and Beck in 1965

A decayed fir stump, 14" dia., bears N.38°W., 23.1 ft., no marks visible.

and a bearing tree mkd. by Jelley and Beck

A fir, 35" dia., bears N.68°E., 36.3 ft., with a healed blaze.

and an accessory by Inman

An iron rod, 5/8" dia., firmly set, with top flush with the surface of the ground for a reference monument, bears N.39°00'49"W, 20.92 ft., with orange plastic cap mkd. INMAN 60050 LS.

and a new bearing tree

A maple, 12" dia., bears S.89°W., 28.2 ft., mkd. ¼ S16 BT. Each new BT has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center & each monument established or remonumented has a magnet deposited in a white plastic case at the base of the stainless steel post. Alum. Angle iron driven alongside each monument.

NAD 1983 (2011)

Latitude: 43°39'24.88" N. Longitude: 123°31'32.92" W.