

PRIMARY CORNER DESCRIPTION Sec Cor for 9, 10, 15 and 16

Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars, Deputy Surveyor under contract # 152 survey dated June 3, 1871 (DCSO records Vol. 4 Pg 1521)  
 -----  
 Set post cor. to secs. 9, 10, 15 and 16, from which  
 A W.Oak 8" dia., bears N.60°E., 8 lks. dist.  
 A Fir 18" dia., bears S.65°E., 6 lks. dist.  
 A W.Oak 10" dia., bears S.30°W., 25 lks. dist.  
 A Laurel 20" dia., bears N.85°W., 4 lks. dist.

---

Wilford Haines - For: Woolley Logging Co. - 9/1960 - M 11-72  
 -----  
 Found - Original bearing trees.  
 Set 1" x 1" x 36" T Iron.  
 Scribe - 28" Fir N.28°W., 23.7 ft.  
 16" Fir N.33°E., 25.0 ft.

---

BLM resurvey by John M. Jelley and Donald Beck, Cadastral Surveyors, under Group #590, surveyed July/Aug. 1965 (DCSO records Vol. 33 Page(s) 13962-63)  
 -----  
 The Sec. cor., perpetuated and recorded by Haines in 1960, monumented with 1" T Iron, firmly set, extending 8" above the ground, with brass disc mkd. Wilford N. Haines 239 Survey Point, Drain Oregon, from which the remaining original bearing trees:  
 A Fir 31" dia., bears S.65°E., 6 lks. dist. no marks evident.  
 A down Madrone 15" dia., bears N.85°W., 4 lks. dist. with old axe marks.  
 and bearing trees marked by Haines  
 A Fir 20" dia., bears N.32¼°E., 37 lks. dist. with scribe marks T22S R7W S10 BT 363 visible on bark blaze.  
 A Fir 30" dia., bears N.28°W., 36 lks. dist. with scribe marks T22 R7W S9 BT 363 visible on bark blaze.  
 At the corner point  
 Set an iron post, 28" long, 2 1/2" dia., 22" in the ground, with brass cap mkd:  

|              |      |
|--------------|------|
| T 22 S R 7 W |      |
| S 9          | S 10 |
| S 16         | S 15 |
| 1965         |      |

 from which new bearing trees  
 An Oak 10" dia., bears S.49½°E., 85½ lks. dist. mkd. T22S R7W S15 BT.  
 A Fir 21" dia., bears S.68°W., 200 lks. dist. mkd. T22S R7W S16 BT.  
 Deposit T iron alongside the iron post.  
 Corner is on a spur, slopes SE

cont

PRIMARY CORNER DESCRIPTION Sec Cor for 9, 10, 15 and 16

|             |                   |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

Fd. OK, May 4, 1989, Les Roberts, C.S. File 63/91 and M 108-22 (Sketch in C.S. File)

Ronald L. Rice, Ward NW - For: Seneca Jones Timber Co. - 12/2003 - M 143-57

-----  
Condition report

Found - 3" BLM BC dated 1965 & 1" T iron  
12" madrone stump N.85°W., 2.6' - no marks  
34" D.Fir bears S.65°E., 4.0' - healed face  
24" D.Fir bears N.32¼°E., 24.4' - bark scribed  
32" D.Fir bears N.28°W., 23.8' - bark scribed  
11" Oak bears S.49½°E., 56.4' - healed face  
26" D.Fir bears S.68°W., 132.0' - healed face  
Note - All corners have a 5½" galvanized steel post adjacent to the cor. monument. Corner accessories have red painted band & face plus yellow BT tag where appropriate.

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2892, surveyed April/May 2018- (DCSO records Vol. 59 Page 23742-3)

-----  
The cor. of secs. 9, 10, 15, and 16, monumented with an iron post, 2½" dia., firmly set, projecting 3" above ground, (alongside of which is a "T" shaped iron rod, ¾" dia., firmly set, projecting 6" above ground, with brass washer mkd. WILFORD N. HAINES 239 SURVEY POINT DRAIN, ORE., with a tack in center) with a brass cap (properly) mkd. from which an original bearing tree

A fir, 36" dia., bears S.65°E., 4.0 ft., with a healed blaze.

and the remains of the bts mkd. by Haines in 1960

A roothole bears N.32¼°E., 24.4 ft., downhill of which is a down fir, 24" dia., with scribe marks 7W S10 BT visible on bark.

A fir, 38" dia., bears N.28°W., 23.8 ft., with scribe marks T22S R7W S9 BT visible on bark.

and a bearing tree mkd. by Jelley and Beck in 1965

A fir, 28" dia., bears S. 68° W., 132.0 ft., with a healed blaze.

and a new bearing tree

A fir, 6" dia., bears N.18¾°E., 29.2 ft., mkd.

Each new BT has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center.