

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 400540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 9 and 10

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars, Deputy Surveyor under contract # 152 survey dated June 3, 1871 (DCSO records Vol. 4 Page(s) 1522)

-----  
Set ¼ sec. post, from which  
    A Fir 36" dia., bears S.40°E., 14 lks. dist.  
    A Fir 24" dia., bears S.1°W., 15 lks. dist.

Fd. in GLO resurvey by Carl Nicklin, Contract #664 dated May 23, 1896 (DCSO records, Vol. 4 page 1550)

Wilford N. Haines - For: Woolley Logging Co. - Sept. 1960  
M 11-72

-----  
Found original bearing trees.  
Set 1" x 1" x 36" T Iron.

Douglas Co. Surveyors Office - Milo E. Godfrey and crew -  
June 11, 1962 - C.S. File 52/14-101

-----  
Found - Haines T Iron and cap at corner.  
    40" Fir S.40°E., 9.2 ft., fragment of old bark  
        scribing visible "¼".  
    40" Fir S.1°W., 9.9 ft., shows good axe scar at  
        bottom (B.T. scar) Haines has reblazed and  
        scribed, in wood, both old BTs.  
New BTs - 15" D.Fir N.75°E., 20.1 ft. mkd. ¼ S10 CS BT.  
          7" D.Fir N.36°W., 28.3 ft. mkd. ¼ S9 CS BT.

Ronald L. Rice, Ward NW - For: Seneca Jones Timber Co. -  
12/2003 - M 143-57

-----  
Found - 1" Haines "T" iron  
    Rec. 40" Fir S.40°E., down.  
    Rec. 40" Fir S.1°W., down.  
    16" D.Fir stump bears N.75°E., 20.1', healed face  
    20" D.Fir bears N.36°W., 28.3', healed face  
New - 16" W.Fir bears S.70°W 23.0', blazed, scribed "¼ S9  
    BT"  
    23" W.Fir bears N.44°W., 11.4', blazed, scribed "¼  
    S9 BT"  
Note - All corners have a 5½" galvanized steel post  
    adjacent to the cor. monument. Corner accessories  
    have red painted band & face plus yellow BT tag  
    where appropriate.