

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 440200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 27 and 34

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by W.H. Byars, Deputy Surveyor under contract # 152 survey dated June 3, 1871 (DCSO records Vol. 4 Page(s) 1530)

-----  
Set ¼ sec. post, from which  
    A Fir 12" dia., bears N.38°E., 22 lks. dist.  
    A Fir 24" dia., bears South, 50 lks. dist.

Wilford N. Haines, #239 - June 29, 1962 - C.S. File 51/222-5

-----  
Found - 24" Fir, South 50.0 lks. now 54" stump. Found T in bark.  
    Position for 12" Fir N.38°E., 22 lks. falls in fire trail built by bulldozer. Found parts of scribe in debris at lower edge of trail about 30 ft. SW of this point.  
Set 1" x 1" x 36" T. Iron.  
Scribed -10" Fir S.29°W., 35.5 ft.  
    Mark X B.O. on rock in place (1 ft. ht. x 3 ft. width), N.65½°W., 123.4 ft.  
This point is N.89°15'E., 2452.1 ft. from sec. cor. 27, 28, 33 and 34.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - V. Tracy and C. Putnam, crew - June 4, 1962 - C.S. File 52/14-10

-----  
Found - Haines T Iron with wooden stake alongside, old piece of wood with good reverse scribing is nailed to wooden stake, could not find where it came from.  
54" Fir stump bears South, 33.0 ft. No scars or scribing visible. No evidence of chopping found on it.  
No trace could be found of NE BT.  
9" D.Fir recently scribed "¼ S34 BT" bears S.28½°W., 35.8 ft.

BLM resurvey by Wayne L. Rogers and Lance J. Bishop, Cadastral Surveyors, under Group #1160, surveyed April/July 1984 - (DCSO records Vol. 47 Page(s) 18080)

-----  
The ¼ sec. cor., perpetuated and recorded by Haines in 1962, monumented with a 1" T shaped iron rod, firmly set, projecting 8" above ground, from which the remains of an original bearing tree:  
    A sawed Fir stump 60" dia., bears South, 50 lks. dist., no marks visible.  
(Cont. Next Page)

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 440200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 27 and 34

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

and a bearing tree and bearing object mkd. by Haines:  
A Fir 24" dia., bears S.28°W., 54 lks. dist. with healed blaze.

A rock outcrop, 3 x 1 x 1 ft., bears N.66°W., 182 lks. dist., with marks X B0 visible. (Rec. 187 lks.)

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, directly over iron rod, with brass cap mkd: T 22 S R 7 W

1/4 S 27  
      S 34  
      1984

from which a new bearing tree

A Fir 4" dia., bears N.53°W., 55 lks. dist. mkd. X BT.

David Edwards - Crew: B. Miller & E. Sprinkle - 1/5/2015 - C.S. File 65/87-2

-----  
Found - Standard Haines T-iron with no brass washer.  
40" dia. Fir stump bears S.30°E., 16.5'. O.B.T. per Haines.

A 13" dia. Fir with healed blaze bears N.71°E., 19.7'. (Haines BT)

Haines' other two BTs are stumps.

New - A 14" dia. Hemlock scribed "T22S R7W S34 BT" bears S.62°E., 37.5 ft.

A 5" dia. Hemlock scribed "T22S R7W S33 BT" bears S.70°W., 25.1 ft.

A 6 foot steel post is set 2 ft East.

No suitable trees in Section 28.

15°E dec.