

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 22

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

Wilford N. Haines, #239 - For: ? - Date ? - Field book H-221

Set 5/8" rebar.
10" Fir S.03°E., 5.0 ft.
18" Fir S.65°E., 32.0 ft.

Gerald Riley, surveyed for Estate of Seigfried Anderson Jr.
March 1998 - M 128-33

Set - 5/8" x 30" rebar, with cap stamped 'RILEY 705"
New Accessories -
20" Fir, S.9°E., 32.6 ft. scribed "C¼ BT"
16" Fir, N.22°W., 37.7 ft. scribed "C¼ BT"
12" Fir, N.4°E., 50.9 ft. scribed "C¼ BT"
3/8" rebar, with cap #239, N.74°50'30"W., 76.86 ft.

Ken Hoffine - For: Juniper Timber Co - June 2006 - M151-22

We initiated this survey at an iron rod set by Riley for the center ¼ of Sec 22. Riley's references from his iron rod for the C¼ to his record BTs & Haines iron rod did not match with discrepancies of 1.5 to 8 ft in distance & 6° to 52° degrees in bearings. We could not reconcile the differences for an accurate C¼ location of Riley's found iron rod. We therefore tied in the exterior corners of sec 22 as shown to recompute & set the center ¼ for section 22.

Set- 5/8"x40' iron rod with 2½" aluminum cap marked LONE ROCK
TIMBER T22S R7W S22 C¼ 2006 PLS 2291.

18" D.Fir bears S.1½°E, 31.1 ft. scribed C¼ S22 BT & tag
15" D.Fir bears N.56¼°E., 42.5 ft. healed face and tag
12" D.Fir bears N.10¼°W., 36.7 ft. healed face and tag
18" D.Fir bears S.1½°E., 31.1 ft. healed face and tag
5/8" iron rod with alum cap (Riley's cap) bears
S.56°37'45"W., 9.95 ft
5/8" iron rod with Haines washer on top, bears
S.69°15'21"W., 72.87 ft.

Corner lies on steep east facing slope approximately 25 feet north of small draw.