

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. for Sec. 15

Alias	Description
Alias	Description
Alias	Description
Alias	Description

BLM resurvey by John M. Jelley and Donald Beck, Cadastral Surveyors, under Group #590, surveyed July/Aug. 1965 (DCSO records Vol. 33 Page(s) 13965)

Point for the center ¼ sec. cor. of sec. 15, at intersection with the E. and W. center line.

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 22 S R 7 W
C ¼ S 15
1965

from which

A W.Fir 22" dia., bears S.70°E., 18 lks. dist. mkd. C ¼ S15 BT.

A Maple 12" dia., bears N.63°W., 70 lks. dist. mkd. C ¼ S15 BT.

John Hollingsworth - For: Oregon State Parks & Recreation - Feb. 25, 1987 - C.S. File 63/62 and M 104-77

Found - 1965 BLM iron pipe with brass cap, firmly set.
24" W.Fir stump, S.70°E., 11.9 ft. to center. Tree has broken off and rolled down hill, has partially visible scribe marks.

12" rotten Maple log, N.63°W., 46.0 ft. no marks visible.

New BTs -28" Fir S.73°E., 58.6 ft. to 2 finish nails side and center, blazed and scribed "C ¼ S15 BT", attached Parks corner tag.

5" Fir S.64°W., 7.52 ft. to 2 finish nails side and center, blazed and scribed "X BT".

Set orange Carsonite post with decal marked "Property Boundary State Park Land Behind this Sign", 2 ft. SE.