

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 440500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 10 and 15

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W.H. Byars, Deputy Surveyor under contract # 152 survey dated June 3, 1871 (DCSO records Vol. 4 Page(s) 1522)

-----  
Set ¼ sec. post, from which  
A Fir 36" dia., bears N.85°W., 5 lks. dist.  
A Fir 36" dia., bears S.80°E., 28 lks. dist.

Wilford Haines - For: Woolley Logging Co. - 9/ 1960 - M 11-72

-----  
Set 1" x 1" x 36" T. Iron with brass cap inscribed.  
Scribe - 12" Cedar N.56°E., 25.4 ft.  
10" W.Fir S.37°W., 22.8 ft.

Cor. Fd. OK, May 1962, DCSO, M. Godfrey, C.S. File 52/14-11

BLM resurvey by John M. Jelley and Donald Beck, Cadastral Surveyors, under Group #590, surveyed July/Aug. 1965 (DCSO records Vol. 33 Page(s) 13963-64)

-----  
The ¼ sec. cor., reestablished at proportionate distance by Haines in 1960, and recorded with the DCSO, monumented with a 1" T Iron, firmly set, extending 6" above the ground, with brass disc mkd. Wilford N. Haines 239 Survey Point Drain Oregon, from which bearing trees mkd. by Haines:

A Cedar 18" dia., bears N.59½°E., 39 lks. dist. with partly healed blaze.  
A Fir snag 13" dia., bears S.39°W., 38 lks. dist. with partly healed blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 22" in the ground, with brass cap mkd:

T 22 S R 7 W

¼  $\frac{S 10}{S 15}$

1965

from which a new bearing tree

A W.Fir 15" dia., bears S.76°W., 58½ lks. mkd. ¼ S15 BT.  
Deposit T iron alongside the iron post.

Ronald L. Rice, Ward NW - For: Seneca Jones Timber Co. - 12/2003 - M 143-57

-----  
Condition report

Found - 3" BLM BC dated 1965 & 1" T iron.

28" Cedar bears N.59½°E., 25.7', healed face

26" W.Fir bears S.76°W., 38.6' healed face

continued next page

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 440500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 10 and 15

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

Note - All corners have a 5½" galvanized steel post adjacent to the cor. monument. Corner accessories have red painted band & face plus yellow BT tag where appropriate.