

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 447100

PRIMARY CORNER DESCRIPTION Standard 1/4 Cor. Sec. 3 only, T23-7

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 4 Page(s) 1496)

-----  
Set standard ¼ sec. post, from which  
A Fir 36" dia., bears S.10°E., 56 lks. dist.  
A Dogwood 6" dia., bears S.67°W., 63 lks. dist.

Wilford N. Haines - For: E.G. Whipple Mill - March/April 1960  
M 18-33

-----  
Set 1" x 1" x 36" T Iron.  
Scribed -24" R.Cedar S.29°W., 26.5 ft.

BLM resurvey by Wayne L. Rogers and Lance J. Bishop, Cadastral Surveyors, under Group #1160, surveyed April/July 1984 - (DCSO records Vol. 47 Page(s) 18070)

-----  
The standard ¼ sec. cor. of sec. 3, reestablished by Haines in 1960, and is accepted as the corner, monumented with a 1" T shaped iron rod, firmly set, projecting 3" above ground with a washer 1" dia. mkd. Wilford N Haines 239 Survey Point Drain Oregon, from which a bearing tree mkd. by Haines

A Cedar 31" dia., bears S.29°W., 37 lks. dist. with healed blaze. (Rec. 40 lks.)

At the corner point

Set an alum. post, 28" long, 2 1/2" dia., 24" in the ground, directly over iron rod, with alum. cap mkd:

-----  
1/4 S 3  
S C  
T 23 S R 7 W  
1987

from which a new bearing tree

A Fir 11" dia., bears S.73½°E., 18½ lks. dist. mkd. ¼ S3  
SC BT.