

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 500176

PRIMARY CORNER DESCRIPTION C C for Secs. 26 & 35 only (West)

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

GLO survey by Carl S. Nicklin, Deputy Surveyor, under joint contract #664 dated May 23, 1896 (DCSO records Vol. 4 Page(s) 1539)

At a point 374 lks. South of cor. for Secs. 27 and 34 only, I set a sandstone 12x10x5 ins., 8" in the ground, for a closing corner of secs. 35 and 26, mkd. C C on E., with one groove on S. and 2 grooves on E. faces; from which
A Fir 24" dia., bears N.67½°W., 135 lks. dist. mkd. T22S R7W S26 BT.
A Fir 10" dia., bears S.35°E., 37 lks. dist. mkd. T22S R7W S35 BT.

Wilford N. Haines, #239 - For: E.G. Whipple - Oct. 1957 - C.S. File 42/309 and M 1-59

True point for closing corner is S.89°20'W., 1.98 ft. from monument which is not terminus of line.
28" Fir N.30°W., 29.7 ft.
Carved X in bed rock.
Found SE BT.
Set 1" x 1" x 36" iron rod with brass cap inscribed Wilford N. Haines #239 Survey Point.

BLM resurvey by Wayne L. Rogers and Lance J. Bishop, Cadastral Surveyors, under Group #1160, surveyed April/July 1984 - (DCSO records Vol. 47 Page(s) 18075)

Closing cor. of secs. 26 and 35, perpetuated and recorded by Haines in 1957 mkd. X CC on bedrock, from which the remaining original tree:
A Fir 27" dia., bears S.35°E., 37 lks. dist., with healed double blaze.
and a bearing tree mkd. by Haines
A Fir 37" dia., bears N.30°W., 45 lks. dist. with scribe marks T22S R7W BT visible on bark blaze.

Found OK, by Hoffine - Oct. 1995 - M119-78