

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 500200

PRIMARY CORNER DESCRIPTION Sec. cor. for 27 & 34 only (E. side)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by W.H. Byars, Deputy Surveyor under contract # 152 survey dated June 3, 1871 (DCSO records Vol. 4 Page(s) 1530)

-----  
Set post cor. to secs. 26, 27, 34 and 35, from which  
A Fir 36" dia., bears N.50°E., 10 lks. dist.  
A Fir 30" dia., bears S.15°E., 45 lks. dist.  
A Fir 30" dia., bears S.72°W., 21 lks. dist.  
A Fir 30" dia., bears N.60°W., 73 lks. dist.

GL0 survey by Carl S. Nicklin, Deputy Surveyor, under joint contract dated May 23, 1896 (DCSO records Vol. 4 Page(s) 1538)

-----  
The cor. of secs. 26, 27, 34 and 35, which is a post, 4" sq., 24" above ground; all the bearing trees standing except that in sec. 27; I reestablish this cor. at same point as follows:  
Set a Fir post, 3 ft. long, 4" sq., 24" in the ground for cor. of secs. 27 and 34, mkd. T22S S34 on SW.; and R7W S27 on NW. faces, with 2 notches on E. and 1 notch on S. edge; from which  
A Fir 24" dia., bears S.72°W., 30 lks. dist. mkd. T22S R7W S34 BT.  
A Fir 40" dia., bears N.65°W., 16 lks. dist. mkd. T22S R7W S27 BT.

Wilford N. Haines, #239 - For: E.G. Whipple - Oct. 1957 - C.S. File 42/309 and M 1-59

-----  
Set 1" x 1" x 36" Iron rod with brass cap inscribed "Wilford N. Haines #239 Survey Point"  
8" Fir N.58°W., 26.5 ft.  
18" Fir S.77°W., 29.5 ft.

BLM resurvey by Wayne L. Rogers and Lance J. Bishop, Cadastral Surveyors, under Group #1160, surveyed April/July 1984 - (DCSO records Vol. 47 Page(s) 18075-76)

-----  
The Sec. cor., reestablished and recorded by Haines in 1957, and is accepted as the corner, monumented with a 1" T shaped iron rod, firmly set, projecting 15" above ground, with a washer 1" dia., mkd. Wilford N Haines 239 Survey Point Drain Oregon. from which the remains of bearing trees mkd. by Haines  
A Fir 26" dia., bears S.76½°W., 45 lks. dist. with healed blaze.  
(Cont. Next Page)

