

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 500240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 26 and 27

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by W.H. Byars, Deputy Surveyor under contract # 152 survey dated June 3, 1871 (DCSO records Vol. 4 Page(s) 1530)

-----  
Set ¼ sec. post, from which  
A Fir snag 20 ft. high, bears N.60°W., 72 lks. dist.  
A Fir snag 60 ft. high, bears S.65°E., 101 lks. dist.

GL0 survey by Carl S. Nicklin, Deputy Surveyor, under joint contract #664 dated May 23, 1896 (DCSO recs Vol 4 Page 1541)

-----  
At the qr. sec. cor.; post decayed; bearing trees down, I reestablish at same point as follows:  
Set a Fir post 3 ft. long, 4" s., 24" in the ground mkd. ¼ S on W. face, for ¼ sec. cor.; from which  
A Fir 36" dia., bears S.12°E., 130 lks. dist. mkd. ¼ S BT.  
A Fir 36" dia., bears S.22°W., 127 lks. dist. mkd. ¼ S BT.

Wilford N. Haines, #239 - For: E.G. Whipple - Oct. 1957 - C.S. File 42/309 and M 1-59

-----  
Set 1" x 1" x 36" Iron rod with brass cap inscribed "Wilford N. Haines #239 Survey Point".  
6" Fir S.71°E., 21.7 ft.  
36" Fir N.69°W., 103.0 ft.

BLM resurvey by Wayne L. Rogers and Lance J. Bishop, Cadastral Surveyors, under Group #1160, surveyed April/July 1984 - (DCSO records Vol. 47 Page(s) 18076-77)

-----  
The ¼ sec. cor., reestablished and recorded by Haines in 1957, and is accepted as the corner, monumented with a 1" T shaped iron rod, firmly set, projecting 5" above ground with a washer 1" dia., mkd. Wilford N Haines 239 Survey Point Drain Oregon.  
from which the remains of bearing trees mkd. by Haines  
A Fir 25" dia., bears S.72 ¾°E., 33 lks. dist. with healed blaze.  
A Fir 53" dia., bears N.73°W., 156 lks. dist. with scribe marks ¼ S27 BT visible on bark blaze.

At the corner point  
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, directly over iron rod, with brass cap mkd. T 22 S R 7 W  
1/4  
S 27 | S 26  
1984

continued next page

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 500240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 26 and 27

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Ken Hoffine - For: Lone Rock Timber Co. - witnesses: Gary Angiolet & Ignacio Roman - 12/5/2007 - C.S. File 65/60-54

-----  
Found - 1984 BLM Brass cap  
58" D.Fir bears N.73¼°W., 102.0 ft. (rec. N.73°W., 102.96 ft. (156 lks)) healed face & tag.  
New - 19" D.Fir bears S.23¼°W., 45.9 ft. we scribe ¼ S27 BT & tag.  
21" D.Fir bears N.53½°W., 22.3 ft. we scribe ¼ S27 BT & tag.  
Note - Corner lies on North side of dirt road, BLM timber to West & reprod to East.

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2824, surveyed May 2016/March 2018 - (DCSO records Vol. 59 Page(s) 23888)

-----  
The ¼ sec. cor. of secs. 26 and 27, perpetuated by Hoffine, in 2007, monumented with an iron post, 2½" dia., firmly set, with top flush with the surface of the ground, with brass cap (properly) mkd. from which the bearing tree mkd. by Haines in 1957, reported by Rogers and Bishop in 1984  
A fir, 62" dia., bears N.73°W., 103.0 ft., with illegible scribe marks visible on bark.  
and the bearing trees mkd. by Hoffine  
A fir snag, 19" dia., bears S.23¼°W., 45.8 ft., with a healed blaze.  
A fir, 23" dia., bears N.53°W., 22.3 ft., with a healed blaze.  
and a new bearing tree  
A fir, 9" dia., bears N.50½°E., 31.5 ft., mkd. ¼ S 26 BT. Each new BT has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center & each monument established or remonumented has a magnet deposited in a white plastic case at the base of the stainless steel post. Alum. Angle iron driven alongside each monument.