

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 500300

PRIMARY CORNER DESCRIPTION Sec. cor. for 22, 23, 26 and 27

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by W.H. Byars, Deputy Surveyor under contract # 152 survey dated June 3, 1871 (DCSO records Vol. 4 Page(s) 1527)

Set post cor. to secs. 22, 23, 26 and 27, from which
A Fir 30" dia., bears N.12°E., 59 lks. dist.
A Cedar 16" dia., bears S.60°E., 64 lks. dist.
A Fir 36" dia., bears S.10°W., 77 lks. dist.
A Fir 24" dia., bears N.20°W., 48 lks. dist.

GL0 survey by Carl S. Nicklin, Deputy Surveyor, under joint contract #664 dated May 23, 1896 (DCSO records Vol. 4 Page(s) 1541)

At the Sec. cor., cor. destroyed; bearing tree in sec. 26 is the only one to be found; I reestablish the cor., from this bearing tree, as follows:
Set a Fir post, 3 ft. long, 4" sq., 24" in the ground, for a cor. of secs. 22, 23, 26 and 27, mkd. T22S S23 on NE.; R7W S26 on SE.; S27 on SW.; and S22 on NW faces; with 2 notches on S. and E. edges; from which
A Fir 6" dia., bears N.28°E., 38 lks. dist. mkd. T22S R7W S23 BT.
A Cedar 18" dia., bears S.60°E., 64 lks. dit. mkd. T22S R7W S26 BT.
A Fir 48" dia., bears S.24°W., 40 lks. dist. mkd. T22S R7W S27 BT.
A Fir 24" dia., bears N.45°W., 92 lks. dist. mkd. T22S R7W S22 BT.

Wilford N. Haines, #239 - For: E.G. Whipple - Oct. 1957 - C.S. File 42/309 and M 1-59

Set from original BT stump.
Set 1" x 1" x 36" Iron rod with brass cap inscribed "Wilford N. Haines #239 Survey Point"
10" Fir N.30°E., 34.5 ft.
5" W.Fir S.69°E., 28.0 ft.

Douglas Co. Surveyors Office - James Byron, Deputy - Crew, Milo Godfrey; C. Putnam - Feb. 3, 1960 - C.S. File 52/14-4

Found - Haines angle iron and brass cap and 1½" steel shaft at corner.
Both BTs as recorded by Haines, now dead.
New BTs - 52" R.Fir stump bears S.34°W., 40.6 ft. scribed S27 T22S R7W CS BT. (Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 22, 23, 26 and 27

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

5" R.Fir bears N.19°E., 100.5 ft. scribed S23 CS BT.
 18" R.Fir bears N.9°W., 110.7 ft. scribed S22 T22S
 R7W CS BT. (March 1962 report: 18" Fir now down,
 shattered stump only left. L.L.)

BLM resurvey by John M. Jelley and Donald Beck, Cadastral
 Surveyors, under Group #590, surveyed July/Aug. 1965 (DCS0
 records Vol. 33 Page(s) 13950-51)

 The Sec. cor., perpetuated and recorded by Haines in 1958,
 monumented with a 1" T Iron, firmly set, extending 14" above
 the ground, with brass disc mkd. Wilford N. Haines, 239
 Survey Point, Drain Oregon, and with an iron rod, 1½" dia.,
 firmly set, extending 3" above the ground, from which the
 remaining trees by Champman and Nicklin in 1898:

- A burned Fir stump 18" dia., bears N.28°E., 38 lks. dist.
 with no marks remaining.
- A burned Fir stump 42" dia., bears S.24°W., 40 lks. dist.
 with no marks remaining.
- A burned and down Fir 36" dia., bears N.45°W., 92 lks.
 dist. with no marks remaining.

- and bearing trees mkd. by Haines
- A dead Fir 10" dia., bears N.30°E., 53 lks. dist. with
 scribe marks T22S R7W S23 BT visible on unhealed blaze.
 - A dead W.Fir 5" dia., bears S.69°E., 42½ lks. dist. with
 scribe marks T22S R7W S26 BT visible on unhealed blaze.

- and bearing trees mkd. by Byron in 1960
- A Fir 9" dia., bears N.19°E., 152 lks. dist. with double
 healed blaze.
 - A sawed Fir stump 52" dia., bears S.34°W., 61 lks. dist.
 with scribe marks T22S R7W S27 CS BT visible on
 unhealed blaze.
 - A broken Fir stump 18" dia., bears N.9°W., 168 lks. dist.
 with no marks remaining.

At the corner point
 Set an iron post, 28" long, 2 1/2" dia., 24" in the ground,
 with brass cap mkd:

T 22 S R 7 W			
S 22	S 23		
S 27	S 26		
1965			

- from which new bearing trees
- A Cedar 10" dia., bears S.41½°W., 78 lks. dist. mkd. T22S
 R7W S27 BT.
 - A Fir 10" dia., bears N.26°W., 157 lks. dist. mkd. T22S
 R7W S22 BT.
- Deposit local T iron and iron rod alongside the iron post.

PRIMARY CORNER DESCRIPTION Sec. Cor. for 22, 23, 26 and 27

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

BLM resurvey by Wayne L. Rogers and Lance J. Bishop, Cadastral Surveyors, under Group #1160, surveyed April/July 1984 - (DCSO records Vol. 47 Page(s) 18077-78)

The Sec. cor., monumented with an iron post, 2½" dia., firmly set, projecting 8" above ground with 1965 brass cap. from which the remains of bearing trees mkd. by Chapman and Nicklin

A burned Fir stump 18" dia., bears N.28°E., 38 lks. dist. no marks visible.

A burned Fir stump 42" dia., bears S.21°W., 40 lks. dist. no marks visible. (Rec. S.24°W.)

A burned and down Fir, 36" dia., bears N.45°W., 92 lks. dist. no marks visible.

and the remains of bearing trees mkd. by Haines in 1957

A root hole bears N.30°E., 52 lks. dist. with a down Fir alongside 10" dia., with scribe marks T22S R7W S23 BT visible on open blaze.

A root hole bears S.66°E., 42 lks. dist. with a down Fir alongside, 16" dia., with scribe marks T22S R7W S26 BT visible on partially healed blaze.

and the remains of bearing trees mkd. by Byron in 1960

A Fir 18" dia., bears N.19°E., 152 lks. dist. with healed blaze.

A Fir stump 52" dia., bears S.34°W., 62 lks. dist. with scribe marks T22S R7W S27 CS BT.

A Fir stump 18" dia., bears N.9°W., 168 lks. dist. no marks visible.

and bearing trees by Jelley and Beck

A Cedar 17" dia., bears S.43°W., 78 lks. dist., with scribe marks T22S R7W S27 BT visible on partially healed blaze. (Rec. S.41½°W.)

A Fir 16" dia., bears N.26°W., 157 lks. dist., with scribe marks T22S R7W S22 BT visible on partially healed blaze.

and a new bearing tree

A Fir 8" dia., bears S.42½°E., 55 lks. dist., mkd. T22S R7W S26 BT.

Fd. OK, March 1998 by G. Riley - M 128-33

FD. OK by Ken Hoffine - June 2006 - M151-22

continued next page

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 500300

PRIMARY CORNER DESCRIPTION Sec. cor. for 22, 23, 26 and 27

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2824, surveyed May 2016/March 2018 - (DCSO records Vol. 59 Page(s) 23888-9)

The cor. of secs. 22, 23, 26, and 27, monumented with an iron post, 2½" dia., firmly set, projecting 8" above ground (alongside of which is an iron rod, 1½" dia., firmly set, projecting 3" above ground, and a "T" shaped iron rod ¾" dia., firmly set, projecting 5" above ground, with brass washer mkd. WILFORD N. HAINES 239 SURVEY POINT DRAIN, ORE., with a tack in center), with brass cap (properly) mkd. from which the remains of the bearing trees mkd. by Nicklin in 1897, reported by Rogers and Bishop in 1984

A burned fir stump, 18" dia., bears N.28°E., 25.1 ft., no marks visible

A decayed burned stump, size indeterminate, bears S.21°W., 26.4 ft., no marks visible.

and the remains of the bearing trees mkd. by Byron in 1960

A fir, 32" dia., bears N.19°E., 100.3 ft., with a healed blaze.

A fir stump, 52" dia., bears S.34°W., 40.9 ft. with illegible scribe marks visible on partially opened blaze.

and the bearing trees mkd. by Jelley and Beck in 1965, reported by Rogers and Bishop in 1984

A cedar, 28" dia., bears S.43°W., 51.5 ft., with a healed blaze.

A fir, 32" dia., bears N.26°W., 103.6 ft. with a healed blaze.

and a new bearing tree

A fir, 6" dia., bears S.67¼°E., 20.0 ft., mkd. X BT.

Each new BT has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center & each monument established or remonumented has a magnet deposited in a white plastic case at the base of the stainless steel post. Alum. Angle iron driven alongside each monument.

NAD 1983 (2011)

Latitude: 43°38'03.05" N. Longitude: 123°30'22.81" W.