

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 500500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 10, 11, 14 and 15

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by W.H. Byars, Deputy Surveyor under contract # 152 survey dated June 3, 1871 (DCSO records Vol. 4 Page(s) 1518)

Set post cor. to secs. 10, 11, 14 and 15, from which
A Fir 48" dia., bears N.70°E., 34 lks. dist.
A Dogwood 8" dia., bears S.55°E., 38 lks. dist.
A Fir 20" dia., bears S.68°W., 24 lks. dist.
A Fir 30" dia., bears N.10°W., 15 lks. dist.

Wilford N. Haines - For: Woolley Logging Co. - Sept. 1960 - M 11-72

Scribed:
10" Fir N.34°W., 31.2 ft.
7" Fir N.32°E., 39.2 ft.
12" Fir S.74°W., 2.1 ft.

BLM resurvey by John M. Jelley and Donald Beck, Cadastral Surveyors, under Group #590, surveyed July/Aug. 1965 (DCSO records Vol. 33 Page(s) 13956)

The sec. cor., reestablished at proportionate distance by Haines in 1960, and recorded with the DCSO, monumented with a 1" T Iron, firmly set, extending 5" above the ground, with brass disc mkd. Wilford N. Haines 239 Survey Point Drain Oregon, from which bearing trees mkd. by Haines:

A Fir 10" dia., bears N.33°E., 60½ lks. dist. with healed blaze.
A Fir 18" dia., bears S.74°W., 3 lks. dist. with healed blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 22 S R 7 W
S 10 | S 11
S 15 | S 14
1965

from which new bearing trees

A Fir 7" dia., bears S.44°E., 71 lks. dist. mkd. T22S R7W S14 BT.

A Fir 11" dia., bears N.63½°W., 45 lks. dist. mkd. T22S R7W S10 BT.

Deposit T iron alongside the iron post.

continued next page

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 500500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 10, 11, 14 and 15

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2824, surveyed May 2016/March 2018 - (DCSO records Vol. 59 Page(s) 23891)

The cor. of secs. 10, 11, 14, and 15, monumented with an iron post, 2½" dia. firmly set, with top flush with the surface of the ground (alongside of which is a "T" shaped iron rod, ¾" dia., firmly set, projecting 1" above ground with brass washer mkd WILFORD N. HAINES 239 SURVEY POINT DRAIN, ORE., with a tack in center) with brass cap (properly) mkd. from which the bearing tree mkd. by Haines in 1960

A fir, 38" dia., bears S.74°W., 2.0 ft., with a healed blaze.

and the bearing trees mkd. by Jelley and Beck in 1965

A fir, 24" dia., bears S.44°E. 46.9 ft. with a healed blaze.

A fir, 19" dia bears N.63½°W., 29.7 ft., with a healed blaze.

and a new bearing tree

A fir, 19" dia., bears N.26¾°E., 36.5 ft. mkd. T22S R7W S11 BT.

Corner is located alongside the SW BT.

Each new BT has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center & each monument established or remonumented has a magnet deposited in a white plastic case at the base of the stainless steel post. Alum. Angle iron driven alongside each monument.