

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 500540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 10 and 11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by W.H. Byars, Deputy Surveyor under contract # 152 survey dated June 3, 1871 (DCSO records Vol. 4 Pg 1519)

-----  
Set ¼ sec. post, from which  
A Fir 48" dia., bears East, 32 lks. dist.  
A Maple 12" dia., bears N.50°W., 30 lks. dist.

Wilford N. Haines - For: Woolley Logging Co. - Sept. 1960 - M 11-72

-----  
Set 1" x 1" x 36" T Iron.  
Scribe - 5" Fir N.52°W., 4.1 ft.  
12" Fir S.10°E., 11.3 ft.

BLM resurvey by John M. Jelley and Donald Beck, Cadastral Surveyors, under Group #590, surveyed July/Aug. 1965 (DCSO records Vol. 33 Page(s) 13957-58)

-----  
The ¼ sec. cor., reestablished at proportionate distance by Haines in 1960, and recorded with the DCSO, monumented with a 1" T Iron, firmly set, extending 10" above the ground, with brass disc mkd. Wilford N. Haines 239 Survey Point Drain Oregon, from which bearing trees mkd. by Haines:

A Fir 15" dia., bears S.12½°E., 17 lks. dist. with partly healed blaze.  
A Fir 8" dia., bears N.52°W., 6 lks. dist. with partly healed blaze.

At the corner point  
Set an iron post, 28" long, 2 1/2" dia., 23" in the ground, with brass cap mkd:

T 22 S R 7 W  
¼  
S 10 | S 11  
1965

Deposit T iron alongside the iron post.

BLM dependent resurvey by Jeffrey O. Covington, Cadastral Surveyor, under Group No. 2824, surveyed May 2016/March 2018 - (DCSO records Vol. 59 Page(s) 23891)

-----  
The ¼ sec. cor. of secs. 10 and 11, monumented with an iron post, 2½" dia, firmly set, projecting 8" above ground (alongside of which is a "T" shaped iron rod, 3/4" dia., firmly set, projecting 8" above ground, with brass washer mkd. WILFORD N. HAINES 239 SURVEY POINT DRAIN, ORE., with a tack in center), with brass cap (properly) mkd. from which the remains of the bearing trees mkd. by Haines, in 1960, reported by Jelley and Beck in 1965

continued next page

TOWNSHIP 22 RANGE 07 POINT IDENTIFIER # 500540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 10 and 11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A decayed fir stump, 18" dia., bears S.12¼°E., 11.2 ft.  
no marks visible.  
A fir, 26" dia., bears N.52°W 4.0 ft., with a healed  
blaze.  
and a new bearing tree  
A fir, 12" dia., bears S.20½°E., 19.0 ft., mkd. ¼ S11 BT.  
Each new BT has a 2½"x ¼" magnetic nail (Mag Nail) driven at  
the base right side-center & each monument established or  
remonumented has a magnet deposited in a white plastic case  
at the base of the stainless steel post. Alum. Angle iron  
driven alongside each monument.